


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 35 Township Number T 3 S Range Number R 18 E/W
 County: Phillips

Distance and direction from nearest town or city street address of well if located within city?
709 State Street, Phillipsburg, KS

2 WATER WELL OWNER: The Mucklet Corporation
 RR#, St. Address, Box #: Michael Key P.O. Box 2020
 City, State, ZIP Code: Oklahoma City, OK 73126
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 50 ft. ELEVATION: 1423.11
 Depth(s) Groundwater Encountered 1 12 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 14.10 ft. below land surface measured on mo/day/yr 05/27/04
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Vapor abstraction
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs sample was submitted
 Water Well Disinfected? Yes No (No)

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 Blank casing diameter in. to 50 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface -4.2 in., weight lbs./ft. Wall thickness or gauge No. Sch 40 PVC
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 28 ft. to 50 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 1 ft. to 28 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Direction from well? How many feet?
Last Site

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>0.5</u>	<u>Concrete</u>			
<u>0.5</u>	<u>19</u>	<u>Clay, sand, dry, very fine grained</u>			
<u>19</u>	<u>25</u>	<u>Clay, sand, dry, light color, very fine grained</u>			
<u>25</u>	<u>30</u>	<u>Sand, dry, fine grained to coarse</u>			
<u>30</u>	<u>35</u>	<u>Sand, dry, fine to gravel</u>			
<u>35</u>	<u>50</u>	<u>Clay, sand, medium clay, very fine grained</u>			

VOBWA RECEIVED
SEP 24 2004
BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05/25/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 594 This Water Well Record was completed on (mo/day/yr) 8/11/09 under the business name of Coronado Great Plains, Inc. by (signature) [Signature]