THE TOWN	71/361/20/197	XTED WELL		WELL RECOR	U Form W		2a-1212			
1 1		ATER WELL:	Fraction SE 1/	on 4/	CV-7 4/	Section Number	1		Range Nun	-
	Phillips		SE ¼	SE ¼	SW ¼	26	T 3	s	R 18	₽ / W
		on from nearest town	or city street a	aaress of well if	ocated within	city?				
1	-	psburg, Kansas								
		WNER: Tom's Ko								
RR#, St. Address, Box# : 444 8th Street Board of Agriculture, Division of Water Resources										
City, Stat	e, ZIP Code		rg, Kansas 6				Application Nu	mber:		
3 LOCA	TE WELL'S	LOCATION 4	DEPTH OF CO	MPLETED WELL	50.	ft. ELE	VATION:	1	1927	
- WITH	-	ECTION BOX:	epth(s) Groundw	rater Encountere	ed 1		t. 2		3	
T 1		N W	FIL'S STATIC	MATER LEVEL	39.68	ft below land	surface measured of	n moldaulu	6/2/09	
🕇		''	Pump	test data: \Moli	ozkoa	NA 4	after	in inoruay/y	1 01.4190	* · · · · · ·
	NW	NE E	Fultipi N.A. Nation	estuala. VVeli	water was	π.:	arter	nours pun	nping	gpm
		Es	t field INA.	gpm: vveii	water was	π.	after	hours pun	nping	gpm
W W		E BO	ore Hole Diamet	er 8 , ir	n. to	.50 ft.,	and			ft.
-] - W		D BE USED AS:						
lı I	sw	SE	1 Domestic	3 Feedlot	6 Oil field	water supply	9 Dewatering	12 (Other (Specify be	elow)
	SVV		2 Irrigation	4 Industrial	7 Lawn ar	nd garden only	10 Monitoring well			. [
	X			pacteriological sa	ample submitt		nt? YesNo.		mo/day/yr samp	le was
<u> </u>		su	bmitted			W	/ater Well Disinfecte	ed? Yes	No 🗸	<u></u>
5 TYPE	OF BLANK	CASING USED:	5	Wrought iron	8 C	oncrete tile	CASING JO	NTS: Glued	Clampe	<u>d</u>
لسسا	Steel	3 RMP (SR)		Asbestos-Cerr		ther (specify be			ed	I .
(2)F	PVC	4 ABS		Fiberglass				Threa	ded.	
Blank casing diameter										
Casing height above land surface2.76 in., weight										
l · · ·			-							1
	Steel	3 Stainless ste		Fiberglass		RMP (SR)				
	Brass	4 Galvanized		Concrete tile	9	ABS	12 Nor	e used (ope	en hole)	
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)										
1 Continuous slot (3) Mill slot 6 Wire wrapped 9 Drilled holes										
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From 35 ft. to										
From										
GRAVEL PACK INTERVALS: From 33 ft. to										
			From	ft. 1	to	ft., F	rom	ft. ·	to	ft
e GROU	T MATERIA			Cement grout			4 Other			
		m			, U	4 4 33	4 Culei		e	
SAULTINE	ervais. From	ource of possible co		IL, FIOIII						
		•							pandoned water v	vell
	otic tank	4 Lateral li					Fuel storage 15 Oil well/Gas well			
	ver lines	5 Cess po	_				12 Fertilizer storage (16) Other (specify below)			
1	tertight sewe	er lines 6 Seepage	pit 9 Feedyard				13 Insecticide storage			
	from well?	Southeast				How ma	any feet? 100			
FROM	10		LITHOLOGIC LO)G	FRO	м ю	PL	UGGING IN	TERVALS	
0	6	Clay, Dark Brov	vn							
6	33	Clay, Brown							- Company Comp	
33	50	Clay, Brown								
										
	_									
		l								
	<u> </u>									
			,				MW4 , Tag # 00260	680 , Flush	mount	
	†			· · · ·			Project Name: Ton			
L	 						GeoCore # 617, KI		74 721	
7 CONTI	DAOTOSS S		OFDE CATA	All This star	- 11					
and was completed on (mo/day/year)										
								ر (day/yr)	/ ₂ 6/.1.7/98.	
under the	business na	ame of	GeoCore	Services, Inc	<u>. </u>	by (sign	ature)	rd Kol	<u> </u>	
INSTR Depar	RUCTIONS: Us tment of Health	e typewriter or ball point p and Environment, Bureau	en. <i>PLEASE PRE</i> ı of Water, Topeka,	SS FIRMLY and PRI Kansas 66620-0001	INT clearly. Plea . Telephone: 91	ase fill in blanks, und 3-296-5545. Send o	derline or circle the corre	t answers. So	end top three copies in one for your record	to Kansas