4 14 00 17:0	W 05::::==	D.WE.		ATER WELL RECC	OKD Form		KSA 82a-				
			Fraction	, AINA/	NIVA/		on Number		ship Number	Range Nu	
County:		illips m nearest	town or city street				26	T	<b>3</b> s	R 18	W
			t. and Cable R			nin city?					
			feyville Reso								
			9 N. Highway		,			Board o	of Agriculture, Div	vision of Water F	Resources
City State 7	IP Code	Phi	lipsburg, KS	67661					tion Number:	iolon of trater i	.00001000
LOCATE	WELL'S LOC	CATON W	ITH ,								
AN "X" IN	SECTION B	OX:	DEPTH O	F COMPLETED V	WELL :	5.5, 18, 30	0* ft. ELE	VATION:	194	3.50 (FM)	
		-		undwater Encount							
<u>  X</u>	NW	NE		TIC WATER LEVI							
1 1	i l	į	P	ump test data: V	Vell water w	as		ft. after	hours	pumping	gpm
₩ W	++		E Est. Yield	gpm: V	Vell water w	as		ft. after	hours	pumping	gpm
		į	Bore Hole Dia	ameter 6 R TO BE USED A	in. to	37.	5	ft. and	i	n. to	ft.
		SE	WELL WATE	R TO BE USED A	AS: 5 Pub	olic water su	ipply	8 Airc	onditioning 1	11 Injection well	*
<b>↓</b>			1 Dome	estic 3 Feed lot	6 Oil 1	field water s	supply	9 Dew	atering 1	Other (Spec	ity below)
	S		I	tion 4 Industria							
			1	cal/bacteriological	l sample sul	bmitted to D					
			submitted						sinfected? Yes		
_	BLANK CAS			5 Wrought		8 Concre	ete tile	CASIN	IG JOINTS: Glue		nped
1 Ste	el	3 RI	MP (SR)	6 Asbesto					Wel		
2 PVC		4 A		7 Fibergla	SS	Ny	lon Tub	ing	Threa	ided FI	ush
Blank casing	diameter	0.25	in. to	<b>4.5</b> ft., Dia	0.25	in. to	17	ft., Dia	0.25	in. to 29	9 ft.
Casing heigh	nt above land	surface	Flush	in., weight	0.25 i	n. O.D.	lbs./ft	Wall thickr	ness or gauge No		
		ERFORA	TION MATERIAL:				PVC		0 Asbestos-cem		
1 Stee	ei	3 St	ainless steel	5 Fibergla	ss	8	RMP (SR)	1	1 Other (specify	)	
2 Bras		4 6	aivanized steel	6 Concrete	e ille	9	ABS	1	2 None used (or	en hole)	
			NINGS ARE:		5 Gauzeo	• • •		8 Saw		11 None (ope	en hole)
	tinuous slot		3 Mill slot		6 Wire wr			9 Drille			Ì
			4 Key punched		7 Torch c			10 Othe	r (specify)		
	RFORATED				. to	5.5			. 17 ft.		
•	ımeter = 1 i	•	From	29 ft	. to	30	ft.	From	ft.	to	ft.
GRA	VEL PACK I	NTERVAL				0.5		From	. 16 ft.	to 19	ft.
			From		. to	31	ft.	From		to	ft.
	MATERIAL:	1 N	eat cement	2 Cement grou	ıt	3 Bent	tonite	4 Other			
Grout Interva	als From	37.5	ft. to 31	ft. From 28	B ft. to	19	ft. From	16 ft	. to <b>6.5</b> ft.	From 3.5 ft.	to 1. ft.
What is the r		•	ble contamination:					•	14 At		well
•			4 Lateral lin		Pit privy		11 Fue	storage	15 O	il well/ Gas well	
_	ver lines		5 Cess poo		Sewage la	igoon		ilizer storage		ther (specify bel	ow)
	tertight sewer	lines	6 Seepage	pit 9	Feedyard			cticide stora	ge		
Direction from	m well?	CODE	1 3771	HOLOGIC LOG		EDOM	How man	y feet?	DITIOOTEO	NTCDVALO	
0	0.5	CODE	Topsoil	JOEOGIO LOG		FROM	то		PLUGGING I	INTERVALS	
•			Silt, yellow-bro	own to dark vell	ow-			*Note:			
			brown, calcifica	•				Three v	apor monito	ring points	with
0.5	22.5	ML	visible to 7.5'					well scr	een are set	in one bore	hole.
00.5	00.5		Silt with San		clay,						
22.5	26.5	MH	trace vegetation		liast 'li						
26.5 27.5	27.5 32.5	CH MH	Fat Clay, ligh Silt, yellow-bro		ittle silt						
21.0	02.0	14111	Sand, light br		v. fine		1	<del> </del>			
32.5	37.5	SP	grained, little g		,,						
7 CONTRA	CTOR'S OR	LANDOV	NER'S CERTIFIC	ATION: This water	er well was	(1) construc	ted, (2) rec	onstructed,	or (3) plugged und	der my jurisdiction	n and was
completed o	n (mo/day/yr)	)	1'	1/09/08		and th	is record is	true to the b	est of my knowle	dge and belief.	Kansas
-			).	531					complete on (mo	-	/11/08
under the bu	siness name	of	Geotech	nical Service	es Inc.	bv	(signature)	//_//	14		
INSTRU	JCTIONS: PI	ease fill in I	lanks and circle the	correct answers. S	end three co	pies to Kans	as Departme	ent of Health	and Environment, E	Bureau of Water, 1	000 S W
Jacksor	St., Ste. 420,	Topeka, K	ansas 66612-1367.	Telephone: 913-29	96-5545. Se	nd one to WA	ATER WELL	OWNER and	retain one for you	r records.	