

1 LOCATION OF WATER WELL: County: Phillips		Fraction NE 1/4 SE 1/4 NE 1/4		Section Number 27		Township Number T 3 S		Range Number R 18 EW	
Distance and direction from nearest town or city street address of well if located within city? Intersection of Cable Road & Hwy. 183. Phillipsburg, KS PCA-13									
2 WATER WELL OWNER: Phillipsburg Coop Assoc.		RR#, St. Address, Box # : P.O. Box 624 City, State, ZIP Code : Phillipsburg, Ks.							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION: 1951.34 (PVC) Depth(s) Groundwater Encountered 1. 42 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 5/8 in. to 55 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No XX ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No XX							
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 2 in. to 30 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 22 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded XX							
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 4 Key punched 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)		SCREEN-PERFORATED INTERVALS: From 55 ft. to 30 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 55 ft. to 26 ft., From ft. to ft. From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 bent 3 Bentonite 4 Other Grout Intervals: From 24 ft. to 0 (2) ft., From 26 ft. to 24 (3) ft., From ft. to ft.		What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? Northeast How many feet? 700							
FROM TO LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS					
0	5	Brown silt							
5	10	Brown silt							
10	15	Light brown silt							
15	20	Brown silt							
20	25	Brown silt							
25	30	Light brown sand							
30	35	Brown sand							
35	40	Brown silty sand							
40	45	Brown clay							
45	47	Gray sand							
47	55	Light brown sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04-24-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 07-31-92 under the business name of GeoCore Services, Inc. by (signature) Doc Roll									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									