

1] LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number																																																												
County: Phillips		SE ¼ NE ¼ NE ¼	27	T 3 S	R 18 E W																																																												
Distance and direction from nearest town or city street address of well if located within city? Intersection of Cable Road & Hwy. 183. Phillipsburg, KS PCA-5																																																																	
2] WATER WELL OWNER: Phillipsburg Coop Assoc. RR#, St. Address, Box #: P.O. Box 624 City, State, ZIP Code: Phillipsburg, Ks.																																																																	
Board of Agriculture, Division of Water Resources Application Number:																																																																	
3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4] DEPTH OF COMPLETED WELL... 51 ft. ELEVATION: 1949.27 (PVC)																																																															
N W E S		Depth(s) Groundwater Encountered 1. 41 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter . 7 5/8 in. to . 51 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well PCA-5 Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No XX																																																															
5] TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter . 2 in. to . 31 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface . 0 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From . 51 ft. to . 31 ft., From ft. to ft. GRAVEL PACK INTERVALS: From . 51 ft. to . 29 ft., From ft. to ft. FROM ft. to ft., FROM ft. to ft.																																																																	
6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 bent. 3 Bentonite 4 Other Grout Intervals: From . 25 ft. to . 0 (2) ft., From . 29 ft. to . 25 (3) ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? Northeast How many feet? 50																																																																	
<table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>4.5</td><td>Brown clayey silt</td><td></td><td></td><td></td></tr><tr><td>4.5</td><td>9.5</td><td>Brown clayey silt</td><td></td><td></td><td></td></tr><tr><td>9.5</td><td>14.5</td><td>Brown clayey silt</td><td></td><td></td><td></td></tr><tr><td>14.5</td><td>19.5</td><td>Brown clayey silt</td><td></td><td></td><td></td></tr><tr><td>19.5</td><td>24.5</td><td>Brown clayey silt</td><td></td><td></td><td></td></tr><tr><td>24.5</td><td>29.5</td><td>Clayey silty sand</td><td></td><td></td><td></td></tr><tr><td>29.5</td><td>34.5</td><td>Tan silt</td><td></td><td></td><td></td></tr><tr><td>34.5</td><td>39.5</td><td>Gray sand</td><td></td><td></td><td></td></tr><tr><td>39.5</td><td>51</td><td>Gray sand</td><td></td><td></td><td></td></tr></tbody></table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	4.5	Brown clayey silt				4.5	9.5	Brown clayey silt				9.5	14.5	Brown clayey silt				14.5	19.5	Brown clayey silt				19.5	24.5	Brown clayey silt				24.5	29.5	Clayey silty sand				29.5	34.5	Tan silt				34.5	39.5	Gray sand				39.5	51	Gray sand			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																												
0	4.5	Brown clayey silt																																																															
4.5	9.5	Brown clayey silt																																																															
9.5	14.5	Brown clayey silt																																																															
14.5	19.5	Brown clayey silt																																																															
19.5	24.5	Brown clayey silt																																																															
24.5	29.5	Clayey silty sand																																																															
29.5	34.5	Tan silt																																																															
34.5	39.5	Gray sand																																																															
39.5	51	Gray sand																																																															
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02-28-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 07-31-92 under the business name of GeoCore Services, Inc. by (signature) Dale Robt																																																																	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																	