


**WATER WELL RECORD Form WWC-5 KSA 82a-1212**

LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 Section Number 22 Township Number T 3 S Range Number R 18 EW  
 County: Phillips  
 Name and direction from nearest town or city street address of well if located within city? Farmland Refinery

WATER WELL OWNER: Farmland Petroleum Refining Division  
 #, St. Address, Box #: Box 183 N, P.O. Box 608  
 State, ZIP Code: Phillipsburg, KS 67146  
 Board of Agriculture, Division of Water Resources  
 Application Number:

LOCATE WELL'S LOCATION WITH "X" IN SECTION BOX:  
  
 DEPTH OF COMPLETED WELL: 43 ft. ELEVATION: 1949.4  
 Depth(s) Groundwater Encountered: 1. 33.5 ft. 2. \_\_\_\_\_ ft. 3. \_\_\_\_\_ ft.  
 WELL'S STATIC WATER LEVEL: 33.81 ft. below land surface measured on 08/06/92  
 Pump test data: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
 Est. Yield \_\_\_\_\_ gpm: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
 Bore Hole Diameter: 24 in. to 43 in. and \_\_\_\_\_ in. to \_\_\_\_\_ in.  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well  
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 7 Lawn and garden only 10 Monitoring well B-6  
 Was a chemical/bacteriological sample submitted to Department? Yes \_\_\_\_\_ No  If yes, mo/day/yr sample was submitted \_\_\_\_\_  
 Water Well Disinfected? Yes \_\_\_\_\_ No

TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued \_\_\_\_\_ Clamped \_\_\_\_\_  
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded \_\_\_\_\_  
 Threaded   
 Blank casing diameter: 6 in. to \_\_\_\_\_ ft. Dia. \_\_\_\_\_ in. to \_\_\_\_\_ ft. Dia. \_\_\_\_\_ in. to \_\_\_\_\_ ft.  
 Casing height above land surface: 19 in. weight \_\_\_\_\_ lbs./ft. Wall thickness or gauge No. Schedule 40

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) \_\_\_\_\_  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot .060  
 2 Louvered shutter 4 Key punched  
 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) \_\_\_\_\_

SCREEN-PERFORATED INTERVALS: From 43 ft. to 28 ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 From \_\_\_\_\_ ft. to \_\_\_\_\_ ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 GRAVEL PACK INTERVALS: From 43 ft. to 26 ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 From \_\_\_\_\_ ft. to \_\_\_\_\_ ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

GRAVEL PACK MATERIAL: 1 Neat cement 2 Cement grout 4% bent. 3 Bentonite 4 Other cement grout  
 Put intervals: From 26 ft. to 24 ft. (3) ft., From 24 ft. to 2 ft. (2) ft., From 2 ft. to Surface (4) ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) \_\_\_\_\_  
 How many feet? \_\_\_\_\_

Section from well?		LITHOLOGIC LOG	PLUGGING INTERVALS	
FROM	TO		FROM	TO
0	18	Sandy clayey silt		
18	30	Sandy silty clay		
30	33.5	Sandy clay		
33.5	38.5	Clayey sand		
38.5	43	Sandy clay		

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/29/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 8/26/92 by (signature) Dale A. Kold  
 Under the business name of \_\_\_\_\_

OFFICE USE ONLY