

1	LOCATION OF WATER WELL: County: <u>Norton</u>	Fraction <u>NE 1/4 NE 1/4 SE 1/4</u>	Section Number <u>2</u>	Township Number T <u>3</u> S	Range Number R <u>23</u> EW
---	--	---	----------------------------	---------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1 mile South Norton KS

2	WATER WELL OWNER: RR#, St. Address, Box # : <u>10811 West 71 Street</u> City, State, ZIP Code : <u>Shawnee KS 66203</u>	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4	DEPTH OF COMPLETED WELL <u>78</u> ft. ELEVATION:
---	--	---	--

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 45 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 20 gpm: Well water was 50 ft. after 1 hours pumping 20 gpm

WELL WATER TO BE USED AS:

<input checked="" type="checkbox"/> Domestic	<input type="checkbox"/> Feedlot	<input type="checkbox"/> Oil field water supply	<input type="checkbox"/> Air conditioning	<input type="checkbox"/> Injection well
<input type="checkbox"/> Irrigation	<input type="checkbox"/> Industrial	<input type="checkbox"/> Domestic (lawn & garden)	<input type="checkbox"/> Dewatering	<input type="checkbox"/> 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5	TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
---	----------------------------	----------------	-----------------	--

Blank casing diameter 4" in. to 'ft., Dia in. to 'ft., Dia in. to 'ft.

Casing height above land surface 30 in., weight 160 lbs./ft. Wall thickness or gauge No. 1.73

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
<input checked="" type="checkbox"/> PVC	4 ABS	7 Fiberglass		Threaded

1 Steel	3 Stainless Steel	5 Fiberglass	<input checked="" type="checkbox"/> PVC	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	<input checked="" type="checkbox"/> 3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 58 ft. to 78 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 78 ft., From ft. to ft.

6	GROUT MATERIAL:	1 Neat cement	2 Cement grout	<input checked="" type="checkbox"/> Bentonite	4 Other
---	-----------------	---------------	----------------	---	---------------

Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	Sandy Clay			
20	30	Fine Sand			
30	51	Coarse Sand			
51	65	Coarse Sand + Blue med			
65	75	Med Gravel			
75	78	Shale			

7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>05/27/05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>701</u> This Water Well Record was completed on (mo/day/yr) <u>05/26/05</u> under the business name of <u>Wilcox Well Drilling</u> by (signature) <u>Mark Perdue</u>
---	--