

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Norton, Fraction SW 1/4 NW 1/4 NE 1/4, Section Number 8, Township Number T 3 S, Range Number R 25 EW. Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Dennis Lechliter, RR#, St. Address, Box #: R.R. 1, City, State, ZIP Code: Clayton, KS. Elevation, Datum, Data Collection Method.

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: A 4-quadrant grid with NW, NE, SW, SE labels.

4 DEPTH OF COMPLETED WELL: 133 ft. Depth(s) Groundwater Encountered (1) 7.8 ft. (2) ... (3) ... WELL'S STATIC WATER LEVEL: 7.8 ft. below land surface measured on mo/day/yr. 7-5-13. Pump test data: Well water was ... ft. after ... hours pumping ... gpm. Est. Yield 107 gpm: Well water was ... ft. after ... hours pumping ... gpm. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Domestic (lawn & garden), 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes ... No ...; If yes, mo/day/yrs Sample was submitted. Water well disinfected? Yes X No

5 TYPE OF CASING USED: 5 Wrought Iron, 8 Concrete tile, CASING JOINTS: Glued X, Clamped, 1 Steel, 3 RMP (SR), 6 Asbestos-Cement, 9 Other (specify below), Welded, 2 PVC, 4 ABS, 7 Fiberglass, Threaded. Blank casing diameter 5 in. to 7.3 ft., Diameter ... in. to ... ft., Diameter ... in. to ... ft. Casing height above land surface 34 in., weight ... lbs./ft. Wall thickness or guage No. 200 PSI

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless Steel, 5 Fiberglass, 7 PVC, 9 ABS, 11 Other (Specify), 2 Brass, 4 Galvanized Steel, 6 Concrete tile, 8 RM (SR), 10 Asbestos-Cement, 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 3 Mill slot, 5 Gauzed wrapped, 7 Torch cut, 9 Drilled holes, 11 None (open hole), 2 Louvered shutter, 4 Key punched, 6 Wire wrapped, 8 Saw Cut, 10 Other (specify). SCREEN-PERFORATED INTERVALS: From 9.3 ft. to 133 ft., From ... ft. to ... ft., From ... ft. to ... ft. GRAVEL PACK INTERVALS: From 2.5 ft. to 133 ft., From ... ft. to ... ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 0 ft. to 2.5 ft., From ... ft. to ... ft., From ... ft. to ... ft. What is the nearest source of possible contamination: 1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 13 Insecticide Storage, 16 Other (specify), 2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 11 Fuel storage, 14 Abandoned water well below, 3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 12 Fertilizer Storage, 15 Oil wll/gas well.

Direction from well? ... How many feet? ... LITHOLOGIC LOG: FROM TO DESCRIPTION FROM TO PLUGGING INTERVALS. 0 4 Black Dirt, 4 35 brown clay, 35 70 brown-yellow clay, 70 133 white clay, sand mix, 133 above.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-6-13 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 756. This Water Well Recorded was completed on (mo/day/year) 7-6-13. Under the business name of Callenton Well Service by (signature) Doug Hall.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-