

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Decatur		Se 1/4 NW 1/4 SW 1/4	1	T 3 S	R 29 E/W
Distance and direction from nearest town or city street address of well if located within city?					
South Rodehaven, Oberlin, Kansas					
2 WATER WELL OWNER:		City of Oberlin			
RR#, St. Address, Box #		107 N. Commercial		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code		Oberlin, KS 67746		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 34.0 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 23.0 ft. 2. 3. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 7.5 in. to 34 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 11 Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile	
1 Steel		3 RMP (SR)		6 Asbestos-Cement	
2 PVC		4 ABS		7 Fiberglass	
Blank casing diameter 2.0 in. to 19.0 ft. Dia		Casing height above land surface 0.0 in. weight lbs./ft. Wall thickness or gauge No. Schd 40		CASING JOINTS: Glued Clamped Welded Threaded	
TYPE OF SCREEN OR PERFORATION MATERIAL:		2 PVC		10 Asbestos-cement	
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut	
1 Continuous slot		3 Mill slot		6 Wire wrapped	
2 Louvered shutter		4 Key punched		7 Torch cut	
SCREEN-PERFORATED INTERVALS:		From 34.0 ft. to 19.0 ft.		From 19.0 ft. to 0.0 ft.	
GRAVEL PACK INTERVALS:		From 34.0 ft. to 17.0 ft.		From 17.0 ft. to 0.0 ft.	
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout	
Grout Intervals: From 17.0 ft. to 14.0 ft.		3 Bentonite		4 Other	
What is the nearest source of possible contamination:		1 Septic tank		4 Lateral lines	
2 Sewer lines		5 Cess pool		7 Pit privy	
3 Watertight sewer lines		6 Seepage pit		8 Sewage lagoon	
		9 Feedyard		10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	6" asphalt, silty clay, loam, dark brown, clay, tan, moist, no odor			
5	10	Clay, tan, lean, moist, no odor			
10	15	Clay, medium brown, lean, moist, no odor			
15	20	Clay, medium to dark brown, lean, moist, no odor			
20	25	Sandy clay, dark brown, to dark gray, lean, saturated at 23', no odor			
25	30	Sandy clay, lean, dark gray to blue gray, saturated no odor			
30	35	Sand, tan, fine grain, saturated, no odor			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-14-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 540 This Water Well Record was completed on (mo/day/yr) 1-4-94 under the business name of KPRXX Prairie Land Environmental Remediation, Inc. (signature)					