

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number		Range Number	
County: Decatur		NW 1/4 NW 1/4 NW 1/4	1		T 3 S		R 29 E	
Distance and direction from nearest town or city street address of well if located within city?								
408 W. Frontier Pkwy.								
2 WATER WELL OWNER:		Don Westervelt		Board of Agriculture, Division of Water Resources				
RR#, St. Address, Box # :		408 W. Frontier Pkwy.		#3 Application Number:				
City, State, ZIP Code :								
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION:						
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.						
		WELL'S STATIC WATER LEVEL 88.12 ft. below land surface measured on mo/day/yr						
		Pump test data: Well water was ft. after hours pumping gpm						
		Est. Yield gpm: Well water was ft. after hours pumping gpm						
		Bore Hole Diameter 8 in. to 100 ft., and in. to ft.						
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted						
		Water Well Disinfected? Yes No X						
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped						
1 Steel 3 RMP (SR)		Welded						
2 PVC 4 ABS		Threaded X						
Blank casing diameter 4 in. to 75 ft., Dia		in. to ft., Dia in. to ft.						
Casing height above land surface in., weight 2.071 lbs./ft. Wall thickness or gauge No. 237								
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)								
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From 75 ft. to 100 ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From 68 ft. to 100 ft., From ft. to ft.								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Volclay								
Grout Intervals: From 0 ft. to 68 ft., From ft. to ft.								
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well						
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well								
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Removed Fuel Storage								
Direction from well?		How many feet?						
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								
0 .8 Asphalt								
.8 22 Loess								
22 82 Clay w/Fine Caliche Strks.								
82 93 Sand & Gravel w/Fine Clay Lys.								
93 100 Shale								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-30-93 and this record is true to the best of my knowledge and belief. Kansas								
Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 12-03-93								
under the business name of Woofter Pump & Well, Inc. by (signature) [Signature]								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								