

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Decatur NW		NW ¼ NW ¼ NW ¼ NW ¼	1	T 3 S	R 29 EW
Distance and direction from nearest town or city street address of well if located within city? 408 W. Frontier Pkwy.					
2 WATER WELL OWNER: Don Westervelt RR#, St. Address, Box #: 408 W. Frontier Pkwy. City, State, ZIP Code: Oberlin, Ks. 67740					
Board of Agriculture, Division of Water Resources Application Number: #4					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N +---+---+ X ---+---+ NE SW SE ---+---+ S		4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 88.07 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter .8 to 100 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X Blank casing diameter 4 in. to 70 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 0 in., weight 2.071 lbs./ft. Wall thickness or gauge No. 237 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 70 ft. to 100 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 65 ft. to 100 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Volclay Grout intervals: From 0 ft. to 65 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Removed Fuel Storage Direction from well? How many feet?					
FROM TO LITHOLOGIC LOG			FROM TO PLUGGING INTERVALS		
0	2	Surface			
2	17	Sandy Loess			
17	25	Sandy Clay			
25	60	Clay w/Caliche Strks.			
60	83	Clay & Caliche w/a few sand strks.			
83	94	Sand & Gravel w/Clay Strks.			
94	100	Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-30-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 12-03-93 under the business name of Woofter Pump & Well, Inc. by (signature) Gary G. Woofter					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					