

1 LOCATION OF WATER WELL: County: <u>Decatur</u>	Fraction SE 1/4 NW 1/4 SW 1/4	Section Number <u>1</u>	Township Number T <u>3</u> S	Range Number R <u>29</u> EW
---	----------------------------------	----------------------------	---------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

209 South Rhodehaven

2 WATER WELL OWNER: <u>City of Oberlin</u> RR#, St. Address, Box # : <u>107 West Commercial</u> City, State, ZIP Code : <u>Overlin, KS 67749</u>	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>28</u> ft. ELEVATION: Depth(s) Groundwater Encountered <u>19.90</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8.25</u> in. to <u>28</u> ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes No <u>X</u>
--	--

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2</u> in. to <u>13</u> ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface <u>flush mount</u> in. weight lbs./ft. Wall thickness or gauge No. <u>0.308</u> Inches TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From <u>13</u> ft. to <u>28</u> ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>11</u> ft. to <u>28</u> ft. From ft. to ft.
--

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>1</u> ft. to <u>9</u> ft. From <u>9</u> ft. to <u>11</u> ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>Southeast</u> 13 Insecticide storage 100 dissolved product plume How many feet? <u>100</u>
--

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Dark brown to black fill			
3	4	Light brown to brown silty clay fill			
4	18	Light brown silts			
18	24	Light brown to brown silts			
24	28	Reddish brown silts			
		*flush mount approved by Mr. Don Taylor of Kansas Department of Health and Environment			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-10-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>590</u> This Water Well Record was completed on (mo/day/yr) <u>4-20-96</u> under the business name of <u>Liehs Drilling</u> by (signature) <u>Wesley D. Liehs</u>
