


1 LOCATION OF WATER WELL: County: <u>Rawlins</u>	Fraction <u>SE 1/4 SE 1/4 SE 1/4</u>	Section Number <u>18</u>	Township Number T <u>3</u> S	Range Number R <u>31</u> E <u>(W)</u>
---	---	-----------------------------	---------------------------------	--

Distance and direction from nearest town or city street address of well if located within city?

8 mi SW Herndon KS

2 WATER WELL OWNER: <u>Andy Hanson</u> RR#, St. Address, Box # : <u>RR1</u> City, State, ZIP Code : <u>Herndon KS 67739</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>245</u> ft. ELEVATION:
--	---



N
--NW-- --NE--
W E
--SW-- --SE--
S

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

<input checked="" type="checkbox"/> Domestic	3 Feedlot	6 Oil field water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)	9 Dewatering	12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<input checked="" type="checkbox"/> PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter in. to ft., Dia in. to ft., Dia in. to ft.			Threaded
Casing height above land surface <u>24</u> in., weight <u>200</u> lbs./ft. Wall thickness or gauge No. <u>21.7</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless Steel	5 Fiberglass	<input checked="" type="checkbox"/> PVC
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)
			10 Asbestos-Cement
			11 Other (Specify)
			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	<input checked="" type="checkbox"/> Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
		7 Torch cut	11 None (open hole)
SCREEN-PERFORATED INTERVALS: From <u>225</u> ft. to <u>245</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>245</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite <input checked="" type="checkbox"/>	4 Other
Grout Intervals: From <u>5</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	<input checked="" type="checkbox"/> Fuel storage	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	15 Oil well/Gas well
				16 Other (specify below)
Direction from well? <u>NE</u>				How many feet? <u>150</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Topsoil			
5	140	Clay			
140	168	Medium Gravel			
168	200	Fine Sand + Clay			
200	210	Coarse Sand some gravel			
210	226	Small Gravel			
226	240	Medium Gravel			
240	245	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 11-5-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 701 This Water Well Record was completed on (mo/day/yr) 11-19-04 under the business name of Wilcox Well Drilling LLC by (signature) Mark Kercher