	WATER WELL RECORD Form	WWC-5 KSA 82a-12	212 ID No. MW - 0	5R
1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Rawlins		14 8	T 3 S	R 33 E/W
Distance and direction from nearest town	or city street address of well if located with	nin city?		9
2 WATER WELL OWNER: Ginther	· Oil		· · · · · · · · · · · · · · · · · · ·	
RR#, St. Address, Box # : 103 Pea			Roam of Amiculture Div	vision of Water Resources
City Chata ZID Code . Atwood	L KS 87730		Application Number:	Halon of Water Maddices
3 LOCATE WELL'S LOCATON WITH				
AN A IN SECTION DOX.	DEP IN OF COMPLETED WELL	35 ft. ELEV	ATION:	
N C	Depth(s) Groundwater Encountered 1	ft.	2ft.	3ft.
A I	WELL'S STATIC WATER LEVEL N			
	Pump test data: Well water w			
	Est. Yield gpm: Well water w	/asfi	. after hours	pumpinggpm
¥ W E	Bore Hole Diameter 8 in. to WELL WATER TO BE USED AS: 5 Pub 1 Domestic 3 Feed lot 6 Oil 1	35	ft. and	n. to ft.
	1 Domestic 3 Feed lot 6 Oil 1	ilic water supply field water supply	9 Dewatering 1	12 Other (Specify below)
SW	2 Irrigation 4 Industrial 7 Law	m and garden (domestic	c) 10 Monitoring well	, , , , , , , , , , , , , , , , , , ,
V V	Was a chemical/bacteriological sample sub			
	submitted		ter Well Disinfected? Yes	
5 TYPE OF BLANK CASING USED:	5 Wrought Iron		CASING JOINTS: Glue	
1 Steel 3 RMP (SI				ded
PVC 4 ABS	·			eaded X
	In. to 10 ft Dia	in. to	ft., Dia	in, to ft.
Casing height above land surface	In. to 10 ft., Dia 0 in., weight .7	716 lbs./ft.	Wall thickness or gauge No	.154
TYPE OF SCREEN OR PERFORATION	MATERIAL:	PVC	10 Asbestos-cem	ent
	ss steel 5 Fiberglass	8 RMP (SR)	11 Other (specify))
	ized steel 6 Concrete tile	9 ABS	12 None used (or 8 saw cut	pen hole)
SCREEN OR PERFORATION OPENING	SSARE: 5 Gauzed Will slot 6 Wire wr	wrapped apped	9 Drilled holes	11 None (open hole)
1 Continuous slot 3 N 2 Louvered shutter 4 K		appeu ut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:	From 10 ft. to		from ft.	to ft.
	From ft. to			
GRAVEL PACK INTERVALS:		35 ft. F	rom ft.	to ft.
		ft. F	rom ft.	to ft.
6 GROUT MATERIAL: 1 Neat ce	ement 2 Cement grout	3 Bentonite	4 Other	
Grout Intervals From 0 ft	ement <u>2 Cement grout</u> ft. to <u>1</u> ft. From <u>1</u>	ft. to 8	ft. From	ft. to ft.
What is the nearest source of possible co	ontamination:	10 Lives	tock pens 14 Al	bandoned water well
1 Septic tank	4 Lateral lines 7 Pit privy			il well/ Gas well
2 Sewer lines	5 Cess pool 8 Sewage la	igoon 12 Fertil	izer storage 16 O	ther (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Contaminated Site				
Direction from well?		How many		(ATTEN (A. C.
FROM TO CODE Asp	LITHOLOGIC LOG pait Surface	FROM TO	PLUGGING I	INTERVALS
	rk Brown Silty Clay			
	y, Dark Brown			
	rk Brown to Grey Clay			
	ey Clay			
 				
	# ** ** ** ** ** ** ** ** ** ** ** ** **			
7 CONTRACTOR'S OR LANDOWNER	R'S CERTIFICATION: This water well was	(1) constructed, (2) recor	nstructed, or (3) plugged und	er my jurisdiction and was
completed on (mo/day/yr) 5-23-07 and this record is true to the best of my knowledge and belief. Kansas				
Water Well Contractor's License No.	554	This Water Well R	ecord was completed on (m	o/day/yr) 6-13-07
under the business name of Woofter Pump & Well Inc. by (signature)				
INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W				