

1 LOCATION OF WATER WELL	Fraction	Section Number	Township Number	Range Number
County: <u>RAWLINS</u>	<u>NW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$	<u>17</u>	<u>T</u> <u>3</u> <u>S</u>	<u>R</u> <u>33</u> <u>E</u> <u>10</u>

Distance and direction from nearest town or city? 1 1/3 S 1/8 E MILES ATWOOD
 Street address of well if located within city?

2 WATER WELL OWNER: ART WALKER
 RR#, St. Address, Box #: RR
 City, State, ZIP Code: ATWOOD KS 67730
 Board of Agriculture, Division of Water Resources
 Application Number:

3 DEPTH OF COMPLETED WELL: 57 ft. Bore Hole Diameter: 8 in. to ft., and in. to ft.
 Well Water to be used as:
 Domestic 3 Feedlot 5 Public water supply 6 Oil field water supply 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below)
 Irrigation 4 Industrial 7 Lawn and garden only
 Well's static water level: 40 ft. below land surface measured on month 19 day 79 year
 Pump Test Data NONE: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED:
 Steel 3 RMP (SR) 5 Wrought iron 6 Asbestos-Cement 8 Concrete tile 9 Other (specify below)
 PVC 4 ABS 7 Fiberglass
 Blank casing dia: 5 in. to ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface: 24 in., weight 2.9 lbs./ft. Wall thickness or gauge No: 7/16 O.R. 312
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 Mill slot 12 None used (open hole)
 Screen or Perforation Openings Are:
 Continuous slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)
 Screen-Perforation Dia: 5 in. to ft., Dia in. to ft., Dia in. to ft.
 Screen-Perforated Intervals: From 57 ft. to 47 ft., From ft. to ft., From ft. to ft.
 Gravel Pack Intervals: From 57 ft. to 15 ft., From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: Neat cement Cement grout 3 Bentonite 4 Other
 Grouted Intervals: From 15 ft. to 5 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well
 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well
 Lateral lines 6 Pit privy Livestock pens 12 Insecticide storage 16 Other (specify below)
 Direction from well: S How many feet: 200 ? Water Well Disinfected? Yes No
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample was submitted month day year: Pump Installed? Yes No
 If Yes: Pump Manufacturer's name Model No. HP Volts
 Depth of Pump Intake ft. Pumps Capacity rated at gal./min.
 Type of pump: Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on month 10 day 19 year 79
 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 331
 This Water Well Record was completed on month 6 day 3 year 80 under the business name of HA DRILLING by (signature) Harry A. Beardsley

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	FROM		TO		LITHOLOGIC LOG		LITHOLOGIC LOG	
	FROM	TO	FROM	TO	FROM	TO	FROM	TO
	0	3	TOP SOIL					
	3	17	CLAY					
	17	25	ROCK					
	25	40	CLAY & FINE SAND					
	40	55	SAND & GRAVEL					
	55	57	SHALE					

ELEVATION: ft. 3 ft. 4 ft.
 Depth(s) Groundwater Encountered 1 ft. 17 ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.