WATER WELL RECORD							Division of Water Resources App. No.						
1 LOCAT Raw		WATER	R WELL:		NW 1/4 SE 1/4	SE ¼	l .	n Number 32	Townshi T	p Number 3 s	Range N	Number □E ⊠w	
Street/Rural A	Address of \			own, dist	ance & direction		Global	Positionin	g System (GPS) inform	nation:		
from nearest town or intersection: If at owner's address, check here □. 5 EAST-2 SOUTH-3 WEST OF ATWOOD							Latitude: (in decimal degrees) Longitude: (in decimal degrees) Elevation:						
2 WATER WELL OWNER Vern Hazlett								Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27					
RR#, St. Address, Box # 2 Ford Drive City, State, ZIP Code Colby, KS 67701							Collection Method: ☐ GPS unit (Make/Model:)						
City, State, Lit Code City, R5 07/01							☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey						
								ccuracy: C <					
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 80 ft.													
	AN "X" IN ON BOX:	4 I	DEPTH OF	COMPLI	OMPLETED WELL 80			ft.					
SECTIO	N BUA: N	WEI	IN(S) GROUND I I 'S STATI	Water End	ountered (1)	· · · · · · · · · ·	ft. (2) ft. (3) ft. ft. below land surface measured on mo/day/yr						
Г 	``	""			a: Well wate								
\w-	NE	EST			pm: Well wate								
w		E WE	LL WATER	TO BE U	O BE USED AS: Public wa			tter supply Geothermal Inje y Dewatering Oth			ion well		
Domestic I					eedlot Oil field water supply			y Dewatering Dt			er (Specify below)		
sw st Irrigation Industrial Domesti													
S If yes, mo/day/yr sample was submitted 1 mile Water Well Disinfected? 🗵 Yes 🗆 No													
					PVC Dothe	or .							
CASING IO	INTS: D	Glued	☐ Clam	ned	□ Welded	Thre	eaded						
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 4.5 in. to 60 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface													
Casing height above land surface 18 in., Weight 2.38 lbs./ft. Wall thickness or gauge No248 TYPE OF SCREEN OR PERFORATION MATERIAL:													
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)													
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)													
SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)													
			Key punched	□ Wi	re wrapped	⊠ Saw	cut	Other (specify)				
SCREEN-PE	ERFORATE	ED INTE	RVALS:	From	60	ft. to	80) ft., F	rom	ft. t	0	ft.	
GRA	VEL PACE	INTER	VAIS	From	20	ft to	80	ft., f	rom	ft :	0	ft.	
J GK	V LL I MOI	· IIVI LIC	V/ILO.	From	20	ft. to	99	ft., F	rom	ft. (io	ft.	
6 GROUT	MATERL	AL: [Neat ceme	nt C	ement grout	X E	Bentonite	☐ Other	•				
Grout Interv	als Fr	om	0 ft. to	20	ement grout ft. From		ft. to	ft	. From		ft. to	ft.	
What is the i	nearest sour	ce of pos	sible contam	ination:	Pit privy		stock pen	_	cticide stora	_		cify below)	
Sew			☐ Cesspool		Sewage lagoon	☐ Fuel			ndoned wate		Miler (spec	iny ociow)	
		r lines	☐ Seepage	oit 🗆 1	Feedyard		lizer stora		well/gas wel	Nor Nor	ıe		
Direction							nce from						
FROM 0	TO 2	Surface		LOGIC L	.OG	FRO)M	TO LITH	O. LOG (co	nt.) <u>or</u> PLUC	JGING IN	NTERVALS	
2	5	Loess											
5	12				caliche strks						-		
20	20 46	Sandstone w/clay & caliche strks Sandy clay w/clay & caliche strks											
46	63	Clay w/fine sand strks											
63	76	Fine & med sand w/clay lenses											
76	80	Black s	shale										
					11.75								
					ERTIFICATI	ON: T							
					(ear) 9/1/11			nd this record				ge and belief.	
			License No.					ord was comp			10/19/11		
under the business name of Woofter Pump & Well Inc. by (signature) INSTRUCTIONS: Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to kansas Department of Health and Environment, Bureau of													
Water, Geolo	gy Section, 1	000 SW J	ackson St., Su	ite 420, To	peka, Kansas 666 od well Visit us a	12-1367.	Telephon	e 785-296 - 552	Send one t	to WATER W	ELL OWN	IER and retain	

Check: ☐ White Copy, ☐ Blue Copy, ☐ Pink Copy