

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County:	Rawlins	NE $\frac{1}{4}$ N $\frac{1}{2}$ $\frac{1}{4}$ N $\frac{1}{2}$ $\frac{1}{4}$	23	T 3 S	R 35 EW

Distance and direction from nearest town or city street address of well if located within city?

2	WATER WELL OWNER:	Lonnie Frick / Hillside Dairy, Inc.	
	RR#, St. Address, Box # :	404 N. 3rd	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	Atwood, Ks. 67730	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

W

N

NE

NW

SE

SW

S

E

4 DEPTH OF COMPLETED WELL 70' ft. ELEVATION:

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 35' ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 in. to 70 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		9 Dewatering
		10 Monitoring well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No ☒; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒

5 TYPE OF BLANK CASING USED:		CASING JOINTS:	
1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)
		7 Fiberglass	
Blank casing diameter <u>4.5</u> in. to <u>50</u> ft., Dia		in. to ft., Dia	
Casing height above land surface <u>18</u> in., weight		<u>2.38</u> lbs./ft. Wall thickness or gauge No. <u>248</u>	
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
			9 ABS
			10 Asbestos-cement
			11 Other (specify)
			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
		7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:			
From <u>50</u>	ft. to <u>70</u>	ft. From	ft. to
From	ft. to	ft. From	ft. to
GRAVEL PACK INTERVALS:			
From <u>20</u>	ft. to <u>70</u>	ft. From	ft. to
From	ft. to	ft. From	ft. to

6] GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:		From 0 ft. to 20 ft.	From	ft. to	ft. to
What is the nearest source of possible contamination:		NONE		10 Livestock pens	14 Abandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage		
Direction from well?				How many feet?	

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-11-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 8-16-95 under the business name of Woofter Pump & Well, Inc. by (signature) [Signature]