


2211025¹⁻⁵ MW-15

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL: County: Republic		Fraction SW 1/4 SW 1/4 NE 1/4	Section Number 16	Township Number T 4 S	Range Number R 1 E (W)
Distance and direction from nearest town or city street address of well if located within city? 50' West of Dales Repair Shop on West Side of East Railroad Street					
2 WATER WELL OWNER: Kansas Department of Health and Environment, Bureau of Remediation RR#, St. Address, Box #: Forbes Field, Building 740 City, State, ZIP Code: Topeka, KS 66620-0001 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"></div>		4 DEPTH OF COMPLETED WELL: 54 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 38.0 ft. below land surface measured on mo/day/yr 06/22/94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes NA No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 (I.D.) in. to 44 ft. Dia. in. to ft. Dia. in. to ft. Dia. in. to ft. Dia. Casing height above land surface 3 ft. weight 0.703 lbs./ft. Wall thickness or gauge No. 0.154 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 54 ft. to 44 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 54 ft. to 40 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 40 ft. to 38 ft. From 38 ft. to 0 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage NA 16 Other (specify below) 13 Insecticide storage NA nitrate spring, carbon tet. spring (furnigant) Direction from well? NA How many feet? NA					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	23	Brown silty clay			
23	54	Fine-med. grained, Tan quartz sand			
54	54 1/2	gray shale (bedrock)			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-18-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 8-10-94 under the business name of GSI by (signature) Allison Irwin					