

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Phillips		NW 1/4 SE 1/4 SW 1/4	26	T 4 S	R 18 E/W
Distance and direction from nearest town or city street address of well if located within city? Approximately 3/4 mile south and 3/4 mile west of Glade					
2 WATER WELL OWNER:		City of Phillipsburg			
RR#, St. Address, Box # :		945 2nd Street			
City, State, ZIP Code :		Phillipsburg, KS 67661			
		Board of Agriculture, Division of Water Resources Application Number: 3,059 & PL 003			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 56 ft. ELEVATION: unknown			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 17. ft. below land surface measured on mo/day/yr 10/16/98			
		Pump test data: Well water was not ch'd. ft. after hours pumping gpm			
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 20 in. to 55.5 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes. No. X. If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded			
2 PVC 4 ABS		7 Fiberglass Threaded			
Blank casing diameter 8 5/8 in. to 45 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 12 in., weight 5.59 lbs./ft. Wall thickness or gauge No. 332					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 45 ft. to 55 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 42 ft. to 55.5 ft. From ft. to ft.					
		From ft. to ft. From ft. to ft.			
		From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL:		50% Sand & 50% Bentonite			
1 Neat cement 2 Cement grout 3 Bentonite 4 Other 50% Sand & 50% Bentonite					
Grout Intervals: From 0 ft. to 4 ft. From 4 ft. to 25 ft. From 25 ft. to 42 ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None known					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil			
3	15	Sand, fine with clay, silty			
15	30	Sand and gravel, fine			
30	32	Clay			
32	40	Sand and gravel, fine, medium with broken limestone			
40	45	Sand with lots of clay			
45	55	Sand and gravel, fine, medium with limestone			
55	55.5	Shale, black			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/16/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 10/21/98					
under the business name of Clarke Well & Equipment, Inc. by (signature) <i>Clarke Well & Equipment, Inc.</i>					