


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Phillips		NE 1/4 SW 1/4 SE 1/4	29	T 4 S	R 18 E/W
Distance and direction from nearest town or city street address of well if located within city? approx. 7/8 mi. ↓ 2 mi. West to Glade, KS.					
2 WATERWELL OWNER:		Well No. 34 (TH 5-88)			
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Application Number: #14892			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 44 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 8' 4" ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 8' 4" ft. below land surface measured on mo/day/yr 4/4/89			
		Pump test data: Well water was 31' 4" ft. after 4 hours pumping 146 gpm			
		Est. Yield 125 gpm: Well water was 47 ft. after hours pumping gpm			
		Bore Hole Diameter 36 in. to 47 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No: If yes, mo/day/yr sample was submitted 10/18/88			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded			
Blank casing diameter 10 in. to 37 ft., Dia		in. to ft., Dia			
Casing height above land surface 3 in., weight		lbs./ft. Wall thickness or gauge No. 365"			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 37 ft. to 47 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 47 ft., From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage			
1 Septic tank 4 Lateral lines 7 Pit privy 8 Sewage lagoon 9 Feedyard		14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit		How many feet? approx. 2600'			
Direction from well? N - NW					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	18	fine to med. sand & gravel			
18	47	fine to coarse sand, gravel with traces of gray clay			
47		gray shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/29/89 and this record is true to the best of my knowledge and belief, Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 4/10/89 under the business name of Layne-Western Co., Wichita, Ks. by (signature) Joe Johnson					