USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

			<u>: 1717</u>				Topeka, Kansas 00020	
1. Location of well:	unty Norton:	Fraction NW 1/4	NW 1/4	SE 1/4	Section	_	Township number Range number 23	
2 Distance and disection		/ FPV 1/4	1/4	_	er of wel		T S R E.W	
7 mile south 1 west of Norton, Kansas R.R. or sh					warren marting			
Street address of well loca	ition if in city:	÷			ate, zip	Rt.	Noton, Kansas 67654	
4. Locate with "X" in sec	tion below:	iketch map:		1			6. Bore hole dia. 9 in. Completion date Well depth 130 ft. 11/11/75	
i !							7 Cable tool x_ Rotary Driven Dug	
NW		re well ildings i	in vici	ni tv			Hollow rod Jetted Bored Reverse rotary	
W W W	E	TIGINGS 1	111 4101	.III UJ			8. Use: Domestic Public supply Industry	
-  -  -	1						Irrigation Air conditioning Stock Lawn Oil field water Other	
SW	SE						9. Casing: Material RMP Height: Above or padges.	
1	1						Threaded Welded Surface 12 in.	
S 1 Mile —							RMP_X PVC Weight 180 lbs./ft. Dia.5 in. to 110 ft. depth Wall Thickness: inches or	
5. Type and color of mate	rial	········			From	То	Diain. to ft. depth gage No. <u>450</u>	
		<del></del>					10. Screen: Manufacturer's name	
Black	k clay				0	4	Type PVC Dia. 5	
Sand					4	21	Slot/gauze_slot Length 20	
Sand					-	21	Set between 110 ft. and 130 ft.	
Green	n Clay				21	52	Gravel pack? Yes Size range of materia - 1/8	
Snanc	dy clay, brown				52	70	11. Static water level: mo./day/yr. ft. below land surface Date 10/31/75	
Sand	(medium)				70	73	12. Pumping level below land surfaces:	
Sana	) (medium)				70	(7	91 ft. after 2 hrs. pumping 14 g.p.m.	
Sandy	y clay, brown				73	110	ft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m.	
Tild was	with white sand	rock			110	130	13. Water sample submitted: mo./day/yr.	
FINE	-W1-017	7	===	-			Yes X No Date	
		· .					14. Well head completion: Well seal Pitless adapter 12 Inches above grade	
			<u>)</u>		<u> </u>		15. Well grouted? <u>yes</u>	
		•	r:				With: Neat cement X Bentonite Concrete  Depth: From ft. to ft.	
	-						16. Nearest source of possible contamination: None	
							ft Direction Type	
							17. Pump: Not installed	
					ļ		Manufacturer's name Aermotor  Model number SD5-33 HP 1/3 Volts 230	
							Length of drop pipe 120 ft. capacity 5 g.p.m.	
	111111111111111111111111111111111111111				<u>†                                      </u>		Туре:	
(Use a second sheet if needed)  18. Elevation: 19. Remarks:							Jet Reciprocating Other	
18. Elevation: 19. I	Remarks:	1 0.	1				20. Water well contractor's certification:	
		MITO	)				This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Topography:	241	(10. J	*				John R. Fawcett & Son 167	
Hill	6110	•					Business name License No. Address Box 149 Norton, Kansas	
X Upland							( ) R - 9 - H Wach-	
Valley							Signed Authorized representative	