

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL..... 50 ft. ELEVATION:

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . ☒ . . . Clamped . . .
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded . . .
2 PVC	4 ABS	7 Fiberglass		Threaded . . .

Blank casing diameter . . . 4.5 . . . in. to 30 . . . ft., Dia . . . in. to . . . ft., Dia . . . in. to . . . ft.

Casing height above land surface . . . 18 . . . in., weight . . . 2.38 . . . lbs./ft. Wall thickness or gauge No. . . 248 . . .

TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify) . . .
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	11 None (open hole)
2 Louvered shutter	4 Key punched	7 Torch cut	9 Drilled holes
SCREEN-PERFORATED INTERVALS:		10 Other (specify) . . .	
	From 30 . . . ft. to 50 . . . ft., From . . . ft. to . . . ft.		
	From . . . ft. to . . . ft., From . . . ft. to . . . ft.		
GRAVEL PACK INTERVALS:			
	From 20 . . . ft. to 50 . . . ft., From . . . ft. to . . . ft.		
	From . . . ft. to . . . ft., From . . . ft. to . . . ft.		

[illegible]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.