


1 LOCATION OF WATER WELL: County: Decatur		Fraction Ne 1/4 Ne 1/4 SW 1/4		Section Number 14		Township Number T 4 S		Range Number R 30 E/W																																																																																																	
Distance and direction from nearest town or city street address of well if located within city? 6mi west and 8 mi. south of Oberlin, Kansas																																																																																																									
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		Keith Sauvage and Son,s 412 West Hall Oberlin, Kansas 67749																																																																																																							
Board of Agriculture, Division of Water Resources Application Number:																																																																																																									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. 138 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 104 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 104 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 10 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... x; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes x No																																																																																																							
																																																																																																									
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued x Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 5 in. to 118 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 258 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 118 ft. to 138 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 25 ft. to 138 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																																																																									
6 GROUT MATERIAL: 1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) How many feet? 60 Direction from well? west																																																																																																									
<table border="1" style="width:100%; border-collapse: collapse;"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>27</td><td>top</td><td></td><td></td><td></td></tr><tr><td>27</td><td>31</td><td>sand</td><td></td><td></td><td></td></tr><tr><td>31</td><td>33</td><td>limstone</td><td></td><td></td><td></td></tr><tr><td>33</td><td>38</td><td>fine sand</td><td></td><td></td><td></td></tr><tr><td>38</td><td>48</td><td>limstone and sand stone</td><td></td><td></td><td></td></tr><tr><td>48</td><td>57</td><td>clay</td><td></td><td></td><td></td></tr><tr><td>57</td><td>72</td><td>limstone</td><td></td><td></td><td></td></tr><tr><td>72</td><td>93</td><td>cemented sand</td><td></td><td></td><td></td></tr><tr><td>93</td><td>99</td><td>sand</td><td></td><td></td><td></td></tr><tr><td>99</td><td>101</td><td>sandy clay</td><td></td><td></td><td></td></tr><tr><td>101</td><td>103</td><td>gravel</td><td></td><td></td><td></td></tr><tr><td>103</td><td>120</td><td>clay limstone strips</td><td></td><td></td><td></td></tr><tr><td>120</td><td>130</td><td>clay</td><td></td><td></td><td></td></tr><tr><td>130</td><td>134</td><td>sand</td><td></td><td></td><td></td></tr><tr><td>134</td><td></td><td>shale</td><td></td><td></td><td></td></tr></tbody></table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	27	top				27	31	sand				31	33	limstone				33	38	fine sand				38	48	limstone and sand stone				48	57	clay				57	72	limstone				72	93	cemented sand				93	99	sand				99	101	sandy clay				101	103	gravel				103	120	clay limstone strips				120	130	clay				130	134	sand				134		shale			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																																																				
0	27	top																																																																																																							
27	31	sand																																																																																																							
31	33	limstone																																																																																																							
33	38	fine sand																																																																																																							
38	48	limstone and sand stone																																																																																																							
48	57	clay																																																																																																							
57	72	limstone																																																																																																							
72	93	cemented sand																																																																																																							
93	99	sand																																																																																																							
99	101	sandy clay																																																																																																							
101	103	gravel																																																																																																							
103	120	clay limstone strips																																																																																																							
120	130	clay																																																																																																							
130	134	sand																																																																																																							
134		shale																																																																																																							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-2-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 398 This Water Well Record was completed on (mo/day/yr) 5-25-91 under the business name of Kelley Drilling Co. by (signature) <i>Richard Kelley</i>																																																																																																									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																																																									

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4