

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Decatur	SW $\frac{1}{4}$ NW $\frac{1}{4}$ NW $\frac{1}{4}$	36	T 4 S	R 30 E/W

Distance and direction from nearest town or city street address of well if located within city?

2 MI. north and 13 mi. west of Dresden, Kansas

2 WATER WELL OWNER:	Dan Wasson	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Seldon, Kansas 67757	Application Number:
City, State, ZIP Code :		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED ^{Plugged} WELL: 109 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 96 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 96 ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes ☒ No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to ft., Dia. in. to ft., Dia. in. to ft.			Threaded
Casing height above land surface 36 in., weight lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify) NA
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	11 None (open hole)
2 Louvered shutter	4 Key punched	7 Torch cut	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From NA ft. to NA ft., From ft. to ft.		10 Other (specify) NA	
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 6 ft. to 3 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	NONE
Direction from well?		How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		13 ft. chlorinated sand over the water			
		clay to 6 ft. 3 ft. of cement grout			
		covered to <u>servic</u> top			
			109	83	sand
			83	6	clay
			6	3	cement grout
			3	0	top soil

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) 7-2-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 398 This Water Well Record was completed on (mo/day/yr) 7-20-93 under the business name of Kelley Drilling Co. by (signature) <i>Richard C. Kelley</i>
--