


1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: Decatur		SW 1/4 SE 1/4 NE 1/4		1		T 4 S		R 30 E			
Distance and direction from nearest town or city street address of well if located within city? 6mi south and 5 mi west of Oberlin, Kansas											
2 WATER WELL OWNER: RR#, St. Address, Box # : Raymond Ritter City, State, ZIP Code : Oberlin, Kansas 67749 Board of Agriculture, Division of Water Resources Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF WELL: 25 ft. ELEVATION: 8 ft. Depth(s) Groundwater Encountered 1. 8 ft. 2. 8 ft. 3. 8 ft. WELL'S STATIC WATER LEVEL 8 ft. below land surface measured on mo/day/yr Pump test data: Well water was 8 ft. after 8 hours pumping 8 gpm Est. Yield 8 gpm: Well water was 8 ft. after 8 hours pumping 8 gpm Bore Hole Diameter 8 in. to 8 ft., and 8 in. to 8 ft. WELL WATER 8 USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes 8 No 8 ; If yes, mo/day/yr sample was submitted 8 Water Well Disinfected? Yes 8 No 8								
											
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 8 Clamped 8 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 8 Blank casing diameter 8 in. to 8 ft., Dia 8 in. to 8 ft., Dia 8 in. to 8 ft. Casing height above land surface 8 in., weight 8 lbs./ft. Wall thickness or gauge No. 8 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) 8 SCREEN-PERFORATED INTERVALS: From 8 ft. to 8 ft., From 8 ft. to 8 ft., From 8 ft. to 8 ft. GRAVEL PACK INTERVALS: From 8 ft. to 8 ft., From 8 ft. to 8 ft., From 8 ft. to 8 ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 8 Grout Intervals: From 8 ft. to 8 ft., From 8 ft. to 8 ft., From 8 ft. to 8 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? 8 How many feet? 8											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
										clorex in the water	
										sand to 8 ft.	
										clay to 6 ft.	
										### ## cement grout to 3 ft	
										cut casing of at 3 ft	
										clay dirt to level	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) 10-3-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 398 This Water Well Record was completed on (mo/day/yr) 10-15-96 under the business name of Kelley Drilling Co. by (signature) 8											