



1 LOCATION OF WATER WELL: County: RAWLINS Fraction: NC 1/4 NC 1/4 NW 1/4 Section Number: 26 Township Number: T 4 SE Range Number: R 33 EW

Distance and direction from nearest town or city street address of well if located within city?
4 mi. East 6 mi. South of Atwood, H.S.

2 WATER WELL OWNER:  **Bernard Kanak**
 RR#, St. Address, Box #: R.R. 1 Box 56 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Atwood, KS. 67730-9730 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 231 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 134-231 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 134 ft. below land surface measured on mo/day/yr 11-18-95
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 20+ gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 9 in. to ft., and in. to ft.
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter: 0 in. to 2 1/2 ft., Dia. 4 in. to ft., Dia. in. to ft.
 Casing height above land surface: pitless adp. in., weight SDR21 lbs./ft. Wall thickness or gauge No. 0.076
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 016
 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 213 ft. to 231 ft. From ft. to ft.
 From ft. to ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 24 ft. to 130 ft. From ft. to ft.
 From 135 ft. to 231 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 25 ft. From 130 ft. to 135 ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? South How many feet? 50 feet

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	60	clay			
60	146	SS + clay			
146	182	fine sand			
182	216	band + sandstone			
216	228	med gr.			
228	231	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-18-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 286 This Water Well Record was completed on (mo/day/yr) 12-7-95 under the business name of Wilcox Drilling by (signature) Bob Wilcox