


1 LOCATION OF WATER WELL: Fraction NE 1/4 SE 1/4 NE 1/4 Section Number 13 Township Number T 4 S Range Number R 17 E  
 County: cheyenne  
 Distance and direction from nearest town or city street address of well if located within city?  
6 East 250.0 + Bird City KS

2 WATER WELL OWNER: Garry Seymour  
 RR#, St. Address, Box #: Hci Box 97 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Bird City KS 67731 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 187 ft. ELEVATION: 3510  
 Depth(s) Groundwater Encountered 1. 98 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 98 ft. below land surface measured on mo/day/yr 23 APR 97  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield 10 gpm; Well water was ft. after hours pumping gpm  
 Bore Hole Diameter 8 in. to ft., and in. to ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well STOCK  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
PVC 4 ABS 7 Fiberglass Welded  
 Blank casing diameter 5 in. to 1.67 ft., Dia. in. to ft., Dia. in. to ft.  
 Casing height above land surface 14 in., weight 2.81 lbs./ft. Wall thickness or gauge No. 5DR21  
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 1 Continuous slot 2 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 1.67 ft. to 187 ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 22 ft. to 165 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 22 ft., From ft. to ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
N.A. in PASTURE  
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top soil			
3	33	clay			
33	58	Sand Rock - clay			
58	59	Rock			
59	118	Sand thin clay layers			
118	127	Sand Rock - Sand layers			
127	146	Sandy clay			
146	162	Sand & Gravel			
162	163	Rock			
163	174	Sand & Gravel			
174	178	clay			
178	187	Sand & Gravel			
187	190	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-21-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 187 This Water Well Record was completed on (mo/day/yr) 4-26-97 under the business name of Schoenbrugge Drilling Inc by (signature) [Signature]