

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

CCB **CDB**

1. Location of well: County Cheyenne NE Fraction SW 1/4 SW 1/4 Section number 7 Township number T 4 S Range number R 37 E

2. Distance and direction from nearest town or city: 1 1/2 M south Bird City
Street address of well location if in city: _____
3. Owner of well: Q M Limited
R.R. or street: Allick Cannon
City, state, zip code: 8811 Palaton Rd. Ayrick Colo 80002

4. Locate with "X" in section below: Sketch map: 1 1/2 Miles south Bird City

6. Bore hole dia. 30 in. Completion date 4-77
Well depth 330 ft.
7. Cable tool Rotary Driven Dug
 Hollow rod Jetted Bored Reverse rotary
8. Use: Domestic Public supply Industry
 Irrigation Air conditioning Stock
 Lawn Oil field water Other

5. Type and color of material	From	To
<u>top soil - clay - rock</u>	<u>0</u>	<u>190</u>
<u>fine sand to medium sand</u>	<u>190</u>	<u>200</u>
<u>10' porous rock - strips of clay</u>	<u>200</u>	<u>210</u>
<u>5' porous rock 5' porous rock & clay</u>	<u>210</u>	<u>220</u>
<u>5' loose porous rock 5' gravel</u>	<u>220</u>	<u>230</u>
<u>10' porous rock</u>	<u>230</u>	<u>240</u>
<u>10' porous rock little clay</u>	<u>240</u>	<u>250</u>
<u>5' porous rock 5' porous rock strips of clay</u>	<u>250</u>	<u>260</u>
<u>10' porous rock rock & clay</u>	<u>260</u>	<u>270</u>
<u>5' gravel 5' porous rock rock & clay</u>	<u>270</u>	<u>280</u>
<u>6' gravel 4' porous rock & clay</u>	<u>280</u>	<u>290</u>
<u>3' clay 7' sand & gravel</u>	<u>290</u>	<u>300</u>
<u>10' gravel</u>	<u>300</u>	<u>310</u>
<u>10' gravel</u>	<u>310</u>	<u>320</u>
<u>7 gravel strips of clay 3' shale</u>	<u>320</u>	<u>330</u>
		<u>BROCK 329'</u>

9. Casing: Material Steel Height: Above or below
Threaded Welded Surface 12 in.
RMP PVC Weight 92 lbs./ft.
Dia. 1 1/2 in. to 330 ft. depth Wall Thickness: inches or
Dia. in. to ft. depth gage No. 7
10. Screen: Manufacturer's name W. L. Brown Outriggers
Type free flow Dia. 1 1/2"
3/16" gauze 3/16" Length 40'
Set between: 290 ft. and 330 ft.
 ft. and ft.
Gravel pack? Size range of material 3/4
11. Static water level: 208 ft. below land surface Date 4-77 mo./day/yr.
12. Pumping level below land surfaces:
270 ft. after 3 hrs. pumping 1200 g.p.m.
 ft. after hrs. pumping g.p.m.
Estimated maximum yield 1200 g.p.m.
13. Water sample submitted: mo./day/yr.
Yes No Date
14. Well head completion:
 Pitless adapter 12 inches above grade
15. Well grouted? Puddled clay
With: Neat cement Bentonite Concrete
Depth: From 0 ft. to 10 ft.
16. Nearest source of possible contamination:
ft. Direction Type
Well disinfected upon completion? Yes No
17. Pump: Not installed
Manufacturer's name Western Land Roller
Model number HP Volts
Length of drop pipe 325 ft. capacity g.p.m.
Type:
 Submersible Turbine
 Jet Reciprocating
 Centrifugal Other

18. Elevation: _____
Topography: Hill Slope Upland Valley
19. Remarks: Irrigation well
Privat Sprinkler
20. Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Jack Bone Shullings 1977
Business name License No.
Address McDonald, Ka 67745
Signed Jack Bone Date 5-77
Authorized representative