

CORRECTION(S) TO WATER WELL RECORD (WWC-5)  
(to rectify lacking or incorrect information)

County: Republic

Location listed as:

Section-Township-Range: \_\_\_\_\_

Fraction ( 1/4 1/4 1/4): \_\_\_\_\_

Location changed to:

3-4-5W

SW SW NW

Other changes: Initial statements: owner address submitted as  
70 Box 283

Changed to: should be:  
845 US HWY 36

Comments: \_\_\_\_\_

verification method: notification by owner, to Smith Co. Health Dept.

initials: DT date: 2/27/2012

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726  
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Republic Fraction SW 1/4 SW 1/4 NW 1/4 Section Number 3 Township Number T 4 S Range Number R 5 E (W) Distance and direction from nearest town or city street address of well if located within city? Kackley - West to 40 Road - North 2 1/2 miles on 40 Road - East Side of Road

2 WATER WELL OWNER: Kansas Land & Cattle RR#, St. Address, Box #: PO Box 293 City, State, ZIP Code: Scandia KS 66966 3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 3x3 grid with 'X' in the NW cell] 4 DEPTH OF COMPLETED WELL: 40 ft. Depth(s) Groundwater Encountered (1) 5 ft. WELL'S STATIC WATER LEVEL: 5 ft. below land surface measured on mo/day/yr. Pump test data: Well water was 7 gpm after 3 hours pumping. Est. Yield: 7 gpm. WELL WATER TO BE USED AS: 3 Eedlot. Was a chemical/bacteriological sample submitted to Department? No. Water well disinfected? No.

5 TYPE OF CASING USED: 2 PVC 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 5 in. to 10 ft., Diameter. Casing height above land surface: 18 in., Weight: 2.893 lbs./ft., Wall thickness or gauge No.: 265. TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 11 Other (Specify). SCREEN OR PERFORATION OPENINGS ARE: 3 Mill slot 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 10 ft. to 40 ft. GRAVEL PACK INTERVALS: From 10 ft. to 40 ft.

6 GROUT MATERIAL: 3 Bentonite 4 Other. Grout Intervals: From 0 ft. to 10 ft. What is the nearest source of possible contamination: 1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 13 Insecticide Storage, 16 Other (specify below).

Direction from well? How many feet? LITHOLOGIC LOG PLUGGING INTERVALS

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Tan Clay			
5	10	Brown Clay			
10	20	Tan Clay Sand Stone			
20	30	Yellow-Tan-Black Clay layers			
30	35	Lime Stone Black Clay			
35	40	Lime Stone - Clay - Sand Stone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-21-11 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 480. This Water Well Record was completed on (mo/day/year) 12-28-11 under the business name of Williams Drilling & Inc by (signature) Ron Williams

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells.