WATER WELL RECORD			Form WV	WC-5	Division of Water	r Resources App. No),	
1 LOCATION OF WATER WELL:			Fraction		Section Number	Township No.	Range Number	
Cou	nty: Clo	ud	NW 1/4 SW 1/4 SE	14 NE 14	34	T 5 S	R 2 □E ☑W	
		Address of Well Location; is		Global Positioning				
from nearest town or intersection: If at owner's address, check here Z . Latitude:39,574686								
Longitude: 97.521810 (in decimal degree							(in decimal degrees)	
1					Elevation: 1327 f	t	(in decimal degrees)	
					Datum: WGS 84	4 D7 NIAD 92 🖂	NATA 27	
2 WA	TER W	ELL OWNER: Monte W	Ventz		Collection Method:	i, [2] NAD 65, []	NAD 27	
RR#, Street Address, Box #: 2181 Rye Rd.					GPS unit (Mak	e/Model·)	
City, State, ZIP Code : Concordia, KS 66901					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
					Est. Accuracy: <	3 m, 🔲 3-5 m, 🔲	5-15 m, □ >15 m	
	ATE WI	ELL					**************************************	
i	H AN "X	"IN 4 DEPTH OF C	OMPLETED WELL	, 86	ft.			
SEC	TION BO	OX: Depth(s) Groundwater Encountered (1)						
	Depth(s) Groundwater Encountered (1)							
	Pump test data: Well water wasft. after hours pumping gram							
N	NW SIE EST. YIELD. 40gpm. Well water was							
w	W L E Bore Hole Diameter 9							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
	Irrigation Industrial Domestic-lawn & garden Monitoring well							
—	Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted								
ļ 	l mile		ected? Yes N					
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter								
Casing height above land surface in., Weight 4.31lbs./ft., Wall thickness or gauge No0.214								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From 66 ft. to 86 ft., From ft. to ft.								
From								
GRAVEL PACK INTERVALS: From 21 ft. to .86 ft., From ft. to .ft.								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From 0 ft. to 21 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:								
Septic tank								
Sewer lines								
✓ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well Southeast ☐ Distance from well 100ft								
FROM	TO		CLOC					
0	28	LITHOLOGI	CLUG	FROM	TO LITHO. LO	45 (cont.) or PLUC	GGING INTERVALS	
		Clay- Silty						
28	60	Sand, fine-medium w/ cl						
60	75	Clay w/ creek gravel (sm						
75	84	Creek gravel, medium w						
84	95	Shale, red/green streaks	3					
				*************		·····		
~~~~		······································	<del></del>					
						<del></del>		
				<del></del>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This was all to the second of the second								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo/day/year) .1/26/2016 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No897								
under the	e busines	is name of	YRU COUNTY, ITC.		by (signature) .	gen IV Well	******************	
INSTRUC	LIUNS: Kansas Da	Use typewriter or ball point pen.	PLEASE PRESS FIRMLY a	nd <u>PRINT</u> clear	rly. Please fill in blanks	ind check the correct ar	aswers. Send one copy to	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.  Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								

http://www.kdbeks.gov/waterwell/index.html