

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	Range Number
County:	NORTON	SW ¼ SW ¼ SE ¼	8		T 5 S	R 22 E (N)

Distance and direction from nearest town or city street address of well if located within city?

IN THE CITY OF EDMOND KS

2	WATER WELL OWNER:	RICHARD CROSSER	
	RR#, St. Address, Box # :	HC 63 BOX 84	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	EDMOND KS 67645-9221	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

W

N

NW	NE
SW	SE

S

E

4 DEPTH OF COMPLETED WELL: 48 ft. **ELEVATION:**

Depth(s) Groundwater Encountered 1. 32 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr 8-5-96

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 10 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 10 in. to 48 ft. and in. to ft.

WELL WATER TO BE USED AS:

☒ Domestic	☐ 3 Feedlot	☐ 6 Oil field water supply	☐ 9 Dewatering	☐ 12 Other (Specify below)
☐ 2 Irrigation	☐ 4 Industrial	☐ 7 Lawn and garden only	☐ 10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes.....No. ☒.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒

5] TYPE OF BLANK CASING USED:		3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped ☐	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded ☐	
☒ PVC	4 ABS	7 Fiberglass		Threaded ☐	
Blank casing diameter 5 in. to 28 ft., Dia		in. to ft., Dia in. to ft.			
Casing height above land surface 18 in., weight 160 lbs./ft.		Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:			☒ PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:			5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	☒ Mill slot	6 Wire wrapped	9 Drilled holes		
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)		
SCREEN-PERFORATED INTERVALS:		From 28 ft. to 48 ft.	From ft. to ft.		
		From ft. to ft.	From ft. to ft.		
GRAVEL PACK INTERVALS:		From 20 ft. to 48 ft.	From ft. to ft.		
		From ft. to ft.	From ft. to ft.		

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	☒ Bentonite	4 Other
Grout Intervals:		From 0 ft. to 20 ft.	From	ft. to	ft.
What is the nearest source of possible contamination:				10 Livestock pens	14 Abandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage		
Direction from well?			How many feet?		

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-5-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 444 This Water Well Record was completed on (mo/day/yr) 8-5-96 under the business name of ANDERSON DRILLING by (signature) *Andy Anderson*