WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.		
1 LOCATION OF WATER WELL: County: Norton	Fraction NW ¼ NW ¼ SW ¼ SW ¼	Section Number Township No. Range Number T 5 S R 23 E		
Street/Rural Address of Well Location;		Global Positioning System (GPS) information:		
from nearest town or intersection: If at		Latitude: .39.6429160 (in decimal degrees)		
1 3/4 mile North of the intersection of Hwy 9 and W3 Road		Longitude: -99.9457220 (in decimal degrees)		
1 0/4 Time North of the interession of they o time the time		Elevation:		
2 WATER WELLOWNED.		Datum: WGS 84, NAD 83, NAD 27		
2 WATER WELL OWNER: Don Hazlett RR#, Street Address, Box #: 140 S Adams Ave		Collection Method: GPS unit (Make/Model: Handheld		
at a small	Adams Ave	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
City, State, 211 code . Colby,	KS 67701	Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m		
3 LOCATE WELL				
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL .1.13			
SECTION BOX: Depth(s) Groun	dwater Encountered (1)	ft. (2) ft. (3) f		
N WELL'S STAT	TIC WATER LEVEL!?ft.	below land surface measured on mo/day/yr		
Pum	o test data: Well water was!!.4	ft. after 1 hours pumping 19 gpn		
NW NE	9gpm. Well water was	ft. after hours pumping gpm		
W E Bore Hole Dian	neter !!!	t., andin. toft. er supply		
	T Foodlet	r supply Devetering 7 Other (Specify below		
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well Livestock				
	/bacteriological sample submitted to	Denartment? \(\sigma\) Yes \(\sigma\) No		
	/day/yr sample was submitted			
	nfected? Yes No			
5 TYPE OF CASING USED: ☐ Steel CASING JOINTS: ☑ Glued ☐ Cla				
Casing diameter 5 in to 93	mped weided infeaded	o ft., Diameter in. to f		
Casing diameter .v	in Weight	lbs./ft., Wall thickness or gauge No. SDR 26		
TYPE OF SCREEN OR PERFORATION		osatu, wan unekiess of gaage too		
☐ Steel ☐ Stainless Steel				
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
Continuous slot				
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From				
From				
GRAVEL PACK INTERVALS: From 22 ft. to113 ft., From ft. to				
From				
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other				
Grout Intervals: From .0				
What is the nearest source of possible contamination:				
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)				
Sewer lines Cesspool	Sewage lagoon Fuel storage			
Di il cont	pit Feedyard Fertilizer st	orage Oil well/gas well Existing Well from well15. faet		
FROM TO LITHOLOG		TO LITHO. LOG (cont.) or PLUGGING INTERVAL		
See Attached Log	Sie Loo	To Elitio. Bod (cont.) of The Conto Intractivity		
Oce Attached Log				
	,			
7 CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATION: This water	r well was 🛮 constructed, 🗌 reconstructed, or 🔲 plugged		
under my jurisdiction and was completed on (mo/day/year) .04/20/20.10 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License N	Io. 433 This Water Well Re	ecord was completed on (mo/day/year) 5/13/2010		
under the business name of Sargent Irri	gation- Holdrege	by (signature) hum Meig		
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.				
		our records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit u		
http://www.kdheks.gov/waterwell/index.html.				
KSA 82a-1212		Check: White Copy, Blue Copy, Pink C		

Sargent Irrigation

WELL AND PUMP SERVICE

PO Box 268 Holdrege, NE 68949 825 Brewster Road

Phone: (308) 995-6143 1-800-860-2946

TEST HOLE LOG

CUSTOMER: Don Hazlett

LOCATION: SW1/4, 5-T5S-R23W, Norton Co., KS

LATITUDE: 39.6429160 **LONGITUDE:** -99.9457220

FOOTAGES: 1292' N of South line & 119' E of West line

DATE: 04/20/2010 DRILLED BY: Kyle Schoff

SWL: 72' **PWL**: 104' **GPM**: 19

from feet	- to feet	
0	20	Asphalt and clay
20	32	Clay
32	40	Fine to medium sand with limestone streaks
40	60	Fine to medium sand with cemented sand
60	80	Fine to medium sand with cemented sand and sandy clay with line strips
80	84	Fine to medium sand with cemented sand with line streaks
84	85	Limestone
85	90	Cemented sand and limestone
90	100	Sandy clay with lime streaks
100	110	Medium to coarse sand and fine gravel
110	111	Limestone
111	120	Yellow ochre and grey shale

Well Information:

Well depth: 113'
Plain casing: 93'
Perf. casing: 20'
Perf. Set: 93'
Casing size: 5"
Slot size: .016"
Gravel: 22-113'
Grout: 0-22'