


1

LOCATION OF WATER WELL:  
County: Norton  
Distance and direction from nearest town or city street address of well if located within city?  
NE corner Main & Washington; Lenor

2

WATER WELL OWNER:  
RR#, St. Address, Box # :  
City, State, ZIP Code :  
Mr. Karol Evans  
Box 187; W Hwy 9  
Lenora, KS 67654

3

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  


4

DEPTH OF COMPLETED WELL: 39.0 ft. ELEVATION: NA  
Depth(s) Groundwater Encountered 1. NA ft. 2. NA ft. 3. NA ft.  
WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr NA  
Pump test data: Well water was NA ft. after NA hours pumping NA gpm  
Est. Yield NA gpm; Well water was NA ft. after NA hours pumping NA gpm  
Bore Hole Diameter 8 in. to NA ft., and NA in. to NA ft.  
WELL WATER TO BE USED AS:  
5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 0 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes NA No X; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes NA No X

5

TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued NA Clamped NA  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded NA  
Blank casing diameter 2 in. to NA ft., Dia. 703 in. to NA ft., Dia. 154 in. to NA ft.  
Casing height above land surface Flush in., weight 703 lbs./ft. Wall thickness or gauge No. 154  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) NA  
12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
7 Torch cut 10 Other (specify) NA  
SCREEN-PERFORATED INTERVALS: From 19.0 ft. to 39.0 ft., From NA ft. to NA ft.  
GRAVEL PACK INTERVALS: From 18.0 ft. to 39.0 ft., From NA ft. to NA ft.

6

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 18.0 ft. to 1.0 ft., From NA ft. to NA ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage  
Direction from well? North How many feet? 200  
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS  
0.0 0.5 Concrete  
0.5 1.0 Silt, sand, clay  
1.0 10.0 Silt, slightly clayey  
10.0 20.0 Silt  
20.0 25.0 Silt, sandy  
25.0 30.0 Sand, fine grain  
30.0 35.0 Silty sand, fine to coarse grain  
35.0 39.0 Sand, fine to coarse, grain, silty  
Flush Mount waiver granted on 10-13-92  
for KDHE NO. 06069495; Lenora Mercantile  
by Don Taylor  
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-19-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 11-25-92 under the business name of GSI by (signature) Alison Irwin

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.