			WATI	ER WELL RECORD	orm WWC-5	KSA 82a	-1212	
LOCAT	ON OF WAT	TER WELL:	Fraction	_	Sect	ion Number	Township Number	Range Number
County: Decatur					1/4	31	T 5 s	R 26 ₽/W
Distance a		_	•	address of well if located	within city?			
1		lż mi. wes	t of Alliso	on				
WATE	R WELL OW							
RR#, St.	Address, Bo		ck Noome					ure, Division of Water Resources
	e, ZIP Code		nnings, Kar		· · · · · · · · · · · · · · · · · · ·		Application Numb	Der: DC 005
LOCAT	E WELL'S L IN SECTION	OCATION WITH	4 DEPTH OF	COMPLETED WELL	7.4	. ft. ELEVA	TION:	No. 3 0018
714 A	IN SECTION	1 BOX.	Depth(s) Ground	dwater Encountered 1.	23	ft. 2	<u>.</u>	ft. 3
7 [1	WELL'S STATIC	C WATER LEVEL	23 ft. be	elow land sur	face measured on mo/da	ay/yr
<u> </u>	NW	NE	Purr	np test data: Well water	was	ft. a	fter hour	s pumping gpm
Est. Yield . 600 . gpm: Well water was ft. after hours pumpin								
Bore Hole Diameter 26 in. to 74							in. toft.	
₹ " [! .	WELL WATER	TO BE USED AS:	5 Public water	supply	8 Air conditioning	11 Injection well
î l	SW	 (F	1 Domestic	3 Feedlot 6	Oil field wat	er supply	9 Dewatering	12 Other (Specify below)
	1		2 Irrigation	4 Industrial	Lawn and g	arden only	10 Monitoring well,	
! L	3	1	Was a chemical	/bacteriological sample s	submitted to Department? \		esNo x ; If	f yes, mo/day/yr sample was sub-
<u> </u>		<u> </u>	mitted			Wa	ter Well Disinfected? Ye	es 🗶 No
TYPE	OF BLANK (CASING USED:		5 Wrought iron	8 Concre	te tile	CASING JOINTS: (Glued x Clamped
1 St	eel	3 RMP (S	iR)	6 Asbestos-Cement		specify below		Welded
2 P\		4 ABS		7 Fiberglass				Threaded
								in. to ft.
Casing he	eight above la	and surface	12	in., weight		Ibs./	ft. Wall thickness or gaug	ge No
TYPE OF	SCREEN O	R PERFORATIO	N MATERIAL:		7 PV		10 Asbestos-	!
1 Steel 3 Stainless steel			s steel	5 Fiberglass	8 RMP (SR)		11 Other (specify)	
2 Brass 4 Galvanize				6 Concrete tile 9 /		3	12 None used	d (open hole)
		RATION OPENIN		RE: 5 Gauzed wrapp				11 None (open hole)
	ontinuous slo		Aill slot		6 Wire wrapped		9 Drilled holes	
	ouvered shut		(ey punched	7 Torch				
SCREEN-	PERFORAT	ED INTERVALS:						ft. toft.
								ft. to
	GRAVEL PA	CK INTERVALS			20			ft. toft.
1			From	ft. to		ft., Fro		ft. to ft.
_	T MATERIAL			2 Cement grout				
				π., From	π 1			ft. toft.
		ource of possible						14 Abandoned water well
1 Septic tank 4 Later				7 Pit privy				
_	ewer lines	5 Cess ver lines 6 Seep	•	8 Sewage lagoon		12 Fertilizer storage 13 Insecticide storage		16 Other (specify below)
				9 Feedyard				
FROM	from well? TO	W	rest LITHOLOGIC	LOG	FROM	How ma		NG INTERVALS
. 0	23	Top			1			
23	57	sand			1			
57	59	blue	mud					
59	73	sand	maa				1137-1981-111-118 X X X	
73	1	shale						
		Silare						
			1					
			/		1			
· -								
7 CONT	BACTOR'S	OR LANDOWNE	B'S CERTIFICAT	FION: This water well we	s(1) constru	ted (2) reco	enstructed or (3) plugger	d under my jurisdiction and was
								ny knowledge and belief. Kansas
				This Water W				
	business na			illing Co.	on noodid wa	•		OSeller
			-		ease fill in blanks			three copies to Kansas Department
				620-7320. Telephone: 913-296-55				