

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Decatur</u>	<u>SW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	<u>11</u>	<u>T 5</u> <u>S</u>	<u>R 28</u> <u>E/W</u>

Distance and direction from nearest town or city street address of well if located within city?

1 1/2 miles north & 1 mile west from Dresden2 WATER WELL OWNER: Sylvester RitterRR#, St. Address, Box # : RR 1 Box 160City, State, ZIP Code : Dresden, Kansas 67635

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>65</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>2.3</u> ft. below land surface measured on mo/day/yr <u>5-2-05</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic <u>X</u> 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC <u>X</u>	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter <u>5</u> in. to <u>6.5</u> ft., Dia			
Casing height above land surface <u>2.4</u> in., weight <u>2.6</u> lbs./ft. Wall thickness or gauge No. <u>1/4</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC <u>X</u>	10 Asbestos-Cement	
1 Steel	8 RMP (SR)	11 Other (Specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless Steel			
4 Galvanized Steel			
5 Fiberglass	5 Guazed wrapped	8 Saw cut <u>X</u>	11 None (open hole)
6 Concrete tile	6 Wire wrapped	9 Drilled holes	
	7 Torch cut	10 Other (specify)	
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot			
2 Louvered shutter			
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From <u>6.5</u> ft. to <u>45</u> ft., From			
GRAVEL PACK INTERVALS: From <u>6.5</u> ft. to <u>20</u> ft., From			

6 GROUT MATERIAL:	1 Neat cement <u>X</u>	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>3</u> ft. to <u>20</u> ft., From				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below) <u>X</u>
			13 Insecticide storage	
Direction from well? <u>north</u>			How many feet? <u>1/4 of a mile</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	top soil			
10	18	clay & sand strip			
18	30	white clay & cement looking rock			
30	45	sand & clay strips			
45	50	white clay & sand			
50	61	very coarse gravel			
61	65	ocher			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-2-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 649 This Water Well Record was completed on (mo/day/yr) 5-17-05 under the business name of Bartell Drilling by (signature)