

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: **Cloud** Fraction: **SE ¼ NE ¼ NW ¼** Section Number: **21** Township Number: **T 5 S** Range Number: **R 3 E/W**

Distance and direction from nearest town or city street address of well if located within city?
3 mi. north of Concordia on Hwy 81

2 WATER WELL OWNER: 81 Texaco
 RR#, St. Address, Box # : **P.O. Box 667**
 City, State, ZIP Code : **Salina, Kansas 67402** ASW-11 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	X		E
S			

4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 1366.30
 Depth(s) Groundwater Encountered 1. ft 2. ft 3. ft
 WELL'S STATIC WATER LEVEL ft below land surface measured on mo/day/yr
 Pump test data: Well water was NA ft after hours pumping gpm
 Est Yield NA gpm: Well water was ft after hours pumping gpm
 Bore Hole Diameter 20 in. to 40 ft, and in. to ft
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning **11** Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring
 Was a chemical/bacteriological sample submitted to Department? Yes. No If yes, mo/day/yr sample was submitted
 Water Well Disinfecta? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded.
 Blank casing diameter 2 in. to 38 ft, Dia in. to ft, Dia in. to ft
 Casing height above land surface 0 in., weight 71.6 lbs./ft. Wall thickness or gauge No. 15.4
TYPE OF SCREEN OR PERFORATION MATERIAL
 1 Steel 3 Stainless steel 5 Fiberglass **7** PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot **3** Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 38 ft to 40 ft, From ft to ft
 From ft to ft, From ft to ft
GRAVEL PACK INTERVALS: From 36 ft to 40 ft, From ft to ft
 From ft to ft, From ft to ft

6 GROUT MATERIAL: 1 Neat cement **2** Cement grout **3** Bentonite 4 Other
 Grout intervals: From 0 ft to 32 ft, From 32 ft to 36 ft, From ft to ft
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy **11** Fuel storage 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)
 Direction from well? How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Clay			
10	15	Sand			
15	40	Clay			

ASW11, Flushmount
 Project Name: GF - 81 Texaco
 KDHE # AS 015 40055

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **(1)** constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/21/2003 and this record is true to the best of my knowledge and belief.
 Kansas Water Well Contractor's License No. **554** This Water Well Record was completed on (mo/day/yr) 4/5/2004
 under the business name of **Woolter Pump & Well, Inc** by (signature) **Jay G. Woolter**

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC
%