


| | | | | |
|---|---|-----------------------------|---------------------------------|-------------------------------|
| 1 LOCATION OF WATER WELL: County: Cloud | Fraction NE 1/4 NE 1/4 SW 1/4 | Section Number 33 | Township Number T 5 S | Range Number R 3 EW |
|---|---|-----------------------------|---------------------------------|-------------------------------|

Distance and direction from nearest town or city street address of well if located within city?
N of 112 E 6th, Concordia

2 WATER WELL OWNER: **KDHE Dry Cleaner Trust Fund**
1006 SW Jackson, Ste 410
 RR#, St. Address, Box # : **Topeka, KS 66612**
 City, State, ZIP Code :
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL **55** ft. ELEVATION: **1371.5**
 Depth(s) Groundwater Encountered 1 **29.5** ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL **29.5** ft. below land surface measured on mo/day/yr **6/17/08**
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) **10** Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No **X**; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No **X**

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded **X**
 Blank casing diameter **2** in. to **40** ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface **0** in., weight lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass **7** PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot **3** Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From **45** ft. to **55** ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From **42.5** ft. to **55** ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement **2** Cement grout **3** Bentonite 4 Other
 Grout Intervals: From **0** ft. to **2** ft., From **2** ft. to **42.5** ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage **16** Other (specify below)
 13 Insecticide storage **Dry Cleaner**
 Direction from well? **South** How many feet? **10**

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|----|--|------|----|--------------------|
| 0 | .2 | Concrete | | | |
| .2 | 1 | Silt, light brown with fine sand, moist | | | |
| 1 | 5 | Fill | | | |
| 5 | 31 | Silt with clay, fine sand, light brown | | | |
| 31 | 35 | Silt with clay, fine sand, light brown moist | | | |
| 35 | 36 | Silt with clay, dark brown with sand | | | |
| 36 | 50 | Medium fine sand, brown with silt | | | |
| 50 | 55 | Med to coarse sand, brown | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **06/05/08** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No **416** This Water Well Record was completed on (mo/day/yr) **6/17/08** under the business name of **Terracon** by (signature) **John J. Galt**