

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Decatur	C 1/4 SW 1/4 NE 1/4	36	T 5 S	R 30 EW

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Doris Slavic	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : Box 294	Application Number: 20080422
City, State, ZIP Code : Kenningston, Ks	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 170 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 ft. 2 na ft. 3 na ft. WELL'S STATIC WATER LEVEL na ft. below land surface measured on mo/day/yr Pump test data: Well water was na ft. after na hours pumping na gpm Est. Yield na gpm: Well water was na ft. after na hours pumping na gpm Bore Hole Diameter 8 in. to 170 ft. and na in. to na ft. WELL WATER TO BE USED AS: 6 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted na Water Well Disinfected? Yes X No na

5 TYPE OF BLANK CASING USED:	5 Wrought Iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 4.5 in. to 130 ft. Dia	in. to na ft. Dia	in. to na ft. Dia	in. to na ft. Dia
Casing height above land surface 18 in., weight 2.38 lbs./ft. Wall thickness or gauge No. 248			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	9 Drilled holes	10 Other (specify)
2 Louvered shutter	4 Key punched	7 Torch cut	
SCREEN-PERFORATED INTERVALS:	From 130 ft. to 170 ft.	From na ft. to na ft.	From na ft. to na ft.
GRAVEL PACK INTERVALS:	From 20 ft. to 170 ft.	From na ft. to na ft.	From na ft. to na ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals From 0 ft. to 20 ft. From na ft. to na ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/ Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	none

Direction from well?	How many feet?
FROM TO CODE LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
0 2 Surface	163 170 Lenses
2 27 Loess	163 170 Yellow ochre/black shale
27 48 Clay & caliche w/sd lenses	
48 69 Fine to some med sd w/clay & Caliche strks	
69 90 Clay & caliche w/sd lenses	
90 103 Caliche w/sdstone & sdstrks	
103 116 Fine to med sd w/caliche strks & clay lenses	
116 119 Caliche	
119 128 Clay & caliche w/sd strks	
128 140 Fine to med sd w/clay & caliche Strks	
140 163 Fine to med sd w/clay & caliche	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATE	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 9/24/08	and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 554	This Water Well Record was completed on (mo/day/yr) 9/30/08	by (signature) [Signature]
under the business name of Woofter Pump & Well Inc.		

INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296 5545. Send one to WATER WELL OWNER and retain one for your records.