

1] LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Rawlins		NW 1/4 SE 1/4 SW 1/4	12	T 5 S	R 33 E(W)
Distance and direction from nearest town or city street address of well if located within city?					
14 miles south & 4 east of Atwood, KS					
2] WATER WELL OWNER: Fred Finley					
RR#, St. Address, Box # : RT. 1					
City, State, ZIP Code : Colby, KS 67730					
Board of Agriculture, Division of Water Resources					
Application Number:					
3] LOCATE WELL'S LOCATION WITHIN AN "X" IN SECTION BOX:					
		4] DEPTH OF COMPLETED WELL: 76 ft. ELEVATION:			
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.		WELL'S STATIC WATER LEVEL: 21 ft. below land surface measured on mo/day/yr			
Pump test data: Well water was ft. after hours pumping gpm		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter: 8 in. to 7.6 ft. and in. to		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No X					
5] TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X Clamped			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Welded			
Blank casing diameter: 4.5 in. to 56 ft. Dia		Threaded			
Casing height above land surface: 18 in., weight 2.38 lbs./ft. Wall thickness or gauge No. 248					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 56 ft. to 76 ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 76 ft. From ft. to ft. From ft. to ft.					
6] GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From ft. to ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination: NONE					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		13 Insecticide storage			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? How many feet?					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 3 Surface					
3 19 Clay					
19 47 Med. sand with clay streaks					
47 55 Sandstone & Clay					
55 68 Clay with sand streaks					
68 70 Ochre					
70 76 Shale					
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-24-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 394 This Water Well Record was completed on (mo/day/yr) 5-7-92 under the business name of WOOFER PUMP & WELL by (signature) Walter Woofers					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					