

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Rawlins	NE 1/4 NE 1/4 SW 1/4	15	T 5 S	R 35 EW

Distance and direction from nearest town or city street address of well if located within city?

11 Miles West of Atwood, Kansas

2 WATER WELL OWNER: Don Argabright	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: Rt. 1	Application Number:
City, State, ZIP Code: Atwood, Kansas 67730	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 190 ft. ELEVATION: NA ft.
	Depth(s) Groundwater Encountered 1. NA ft. 2. NA ft. 3. NA ft.
	WELL'S STATIC WATER LEVEL 136' ft. below land surface measured on mo/day/yr 8-17-89
	Pump test data: Well water was NA ft. after NA hours pumping NA gpm
	Est. Yield NA gpm: Well water was NA ft. after NA hours pumping NA gpm
	Bore Hole Diameter 9 in. to 190 ft., and NA in. to NA ft.
WELL WATER TO BE USED AS:	
<input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Feedlot <input type="checkbox"/> Oil field water supply <input type="checkbox"/> Dewatering <input type="checkbox"/> Other (Specify below) Stockwell <input type="checkbox"/> Irrigation <input type="checkbox"/> Industrial <input type="checkbox"/> Lawn and garden only <input type="checkbox"/> Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes NA No X ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes NA No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped NA
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded NA
Blank casing diameter 5 in. to 170 ft., Dia NA in. to NA ft., Dia NA in. to NA ft.			Threaded NA
Casing height above land surface 18 in., weight 2.81 lbs./ft. Wall thickness or gauge No. 265			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)
5 Fiberglass	6 Concrete tile		
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	11 None (open hole)
2 Louvered shutter	4 Key punched	7 Torch cut	9 Drilled holes
SCREEN-PERFORATED INTERVALS:		10 Other (specify)	
From 170 ft. to 190 ft.	From 170 ft. to 190 ft.		
From 20 ft. to 190 ft.	From 20 ft. to 190 ft.		
GRAVEL PACK INTERVALS:	From 20 ft. to 190 ft.		
From 20 ft. to 190 ft.	From 20 ft. to 190 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft.	From 0 ft. to 20 ft.	From 0 ft. to 20 ft.	From 0 ft. to 20 ft.	From 0 ft. to 20 ft.
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? North		How many feet? 1250		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Surface	151	157	Clay
3	35	Clay	157	178	Caliche
35	36	Caliche	178	183	Med. Sand
36	40	Clay	183	186	Ochre
40	70	Caliche	186	190	Shale
70	72	Clay			
72	85	Fine-Med. Sand			
85	87	Clay			
87	105	Caliche & Cemented Sand			
105	109	Clay			
109	122	Caliche & Clay			
122	137	Med. Sand			
137	140	Cemented Sand Strks			
140	141	Clay			
141	151	Caliche & Sand Strks.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-17-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 394 This Water Well Record was completed on (mo/day/yr) 8-18-89 under the business name of Woofter Pump & Well Service by (signature) <i>Walter Woofter</i>
