

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Rawlins	Fraction NW 1/4 NW 1/4 NW 1/4	Section number 24	Township number T 5 S R	Range number 35	X W
2. Distance and direction from nearest town or city: of Levant, Kansas Street address of well location if in city:				3. Owner of well: Cities Service Gas Company R.R. or street: P. O. Box 25128 City, state, zip code: Oklahoma City, Okla. 73125			
4. Locate with "X" in section below: N W E S 1 Mile		Sketch map: Well No. 1 (TH 1-79)		6. Bore hole dia. 18 in. Completion date Well depth 302 ft. 8/23/79			
5. Type and color of material		From		To		7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary	
Top soil		0		10		8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input checked="" type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
Fine sand		10		15		9. Casing: Material steel Height: Above 24 in. Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 24 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 24.70 lbs./ft. Dia. 8 in. to 272 ft. depth Wall Thickness: inches of Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 0.277	
Brown clay - some sand		15		100		10. Screen: Manufacturer's name Layne & Bowler Type Mild Steel Dia. 8" Slot/gauze #6 Length 30' Set between 272 ft. and 302 ft. <input type="checkbox"/> ft. and <input type="checkbox"/> ft. Gravel pack? Yes Size range of material 1/8x1/4	
Fine sand		100		110		11. Static water level: 183 ft. below land surface Date 8/9/79	
Clay		110		120		12. Pumping level below land surfaces: 220 ft. after 3 hrs. pumping 32 g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 55 g.p.m.	
Fine sand		120		150		13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date	
Clay w/streaks of sandstone		150		160		14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter 24 inches above grade	
Fine sand w/med. gravel		160		187		15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 6 ft. to 26 ft.	
Clay		187		199		16. Nearest source of possible contamination: ft. 2200 Direction East Type Farm Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Fine sand w/few clay streaks		199		299		17. Pump: Not installed Manufacturer's name Jacuzzi Bros. Model number 5SD4 HP 5 Volts 440 Length of drop pipe 263 ft. capacity 30 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
Clay		299		306		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne Western Co. 102 Business name Address 1011 W. Harry Wickham Signed [Signature] Date 8/29/79	
Shale		306		320			
BROCK 306'							
18. Elevation:		19. Remarks: Replaces original well of 5/17/79 which was abandoned					
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley							