USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County Rawlins	Fraction		Section number		number	Township number Range number			
		NE 1/4 NE	1/4 SE	1/4		29	T 5 s	<u> </u>	E.	
2. Distance and direction from nearest town or city: Levant, KS 14½ miles North; 3½ miles West Street address of well location if in city: 3. Owner of well: R.R. or street:							Howard Gene Curry			
City, state, zip code: Le							evant, KS 67743			
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. <u>36</u> in. Completion date Well depth280 ft. <u>10-22-78</u>				
NW NE						7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X_ Reverse rotary				
						8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other 9. Casing: Material Stee1 Height: Above or below Threaded Welded Surface 12 in.				
SW SE										
S S							RMPPVCWeight 31.75_lbs./ft. Dia 16 in. to 280 ft. depth Wall Thickness inches or			
5. Type and color of material From						To	Dia 16 in . to 280 ft . dept Dia in . to ft . dept	h!Wall Thickness: inch	es or	
					110	ļ.,	10. Screen: Manufacturer's n			
Top Soil, Clay, & Gravel Streaks						160	Type Wire Wrapped Dia. 16 Slot/gauze 100 Length 10			
Fine Sand & Sandstone (Layers, Hard)					160	170	Set between 270 Perf (Brown) 190 on	ft. and280	ft.	
Fine Sand & Streaks Sandstone					170	181	Gravel pack? Size ran		ft. L=70 %½x5/	
Fine Sand & Trace Clay				181	205	11. Static water level: 151 ft. below land surf	ace Date 10-16-	day/yr. -78		
Sandstone & Clay (Hard)					205	210	12. Pumping level below land	surfaces:		
Fine Sand & Sandstone					210	220	275 ft. after hrs. pumping 6.36 g.p.m ft. after hrs. pumping g.p.m. Estimated maximum yield 6.36 g.p.m.			
Fine Sand & Medium Gravel (Brown, Loose)					220	256	13. Water sample submitted: mo./day/yr.			
Sandstone					256	257	Yes x No D	Date		
Fine Sand & Medium Gravel (Brown, Loose)					256		Pitless adapter 12 Inches above grade 15. Well grouted? Yes			
Medium Gravel (Loose)					270	278	With:Neat cement Depth: From 0 ft. to _	$_{10}^{\text{Bentonite}}$ $_{10}^{\text{X}}$ Cor	ncrete	
Ochre & Shale RPACK 70K'					278	290	16. Nearest source of possible ft. 3000 Direction W	SW Type <u>Farn</u>		
1 Druck 2/0						Well disinfected upon complet 17. Pump: Manufacturer's name Flows	Not installed			
							Model number 1000M Length of drop pipe 276	_ HP 100 Volts .		
						Type: Submersible	_X_ Turbine			
(Use a second sheet if needed)							Jet Centrifugal	Reciproca	rting S	
18. Elevation:	19. Remarks:						20. Water well contractor's co		aport	
Тороgraphy:						is true to the best of my knowledge and belief. Western Well & Pump. Tnc. 245				
Hill							Business name	Licens	245 × 1	
Slope Upland Valley							Address 852 Colby, KS 67701 Signed Authorized representative			
							7.5о, 1203 Терл			