


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

T R EW sec 1/4 1/4 1/4 No.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County Rawlins	Township name Mineral	Fraction NE 1/4	Section number 6	Town number 5	Range number 36																																																					
Distance and direction from nearest town or city: 12 miles SW of McDonald				3 Owner of well: O A Cooper Address: Hermitville Holdrege, Neb.																																																							
Locate with "X" in section below: 				Sketch map:																																																							
2				4 Well depth: 280 ft. Date of completion 7-1 Well diameter 30 in.																																																							
<table border="1"><thead><tr><th>Type and color of material</th><th>From</th><th>To</th></tr></thead><tbody><tr><td>top soil & clay</td><td>0</td><td>150</td></tr><tr><td>9' coarse gravel 1' sandy clay</td><td>150</td><td>160</td></tr><tr><td>5' sandy clay porous rock 5' gravel little</td><td>160</td><td>170</td></tr><tr><td>5' gravel and porous rock 5' porous rock loose</td><td>170</td><td>180</td></tr><tr><td>5' porous rock loose 5' porous rock little loose</td><td>180</td><td>190</td></tr><tr><td>2' porous rock 3' rock 5' coarse gravel little</td><td>190</td><td>200</td></tr><tr><td>6' gravel and porous rock 4' coarse gravel</td><td>200</td><td>210</td></tr><tr><td>7' sandy clay & clay 3' loose porous rock</td><td>210</td><td>220</td></tr><tr><td>10' loose porous rock</td><td>220</td><td>230</td></tr><tr><td>10' loose porous rock little clay</td><td>230</td><td>240</td></tr><tr><td>3' porous rock & clay 7' clay</td><td>240</td><td>250</td></tr><tr><td>1' clay 8' porous rock, clay, sandy clay 1' sand</td><td>250</td><td>260</td></tr><tr><td>4' med sand porous rock & clay 6' porous rock</td><td>260</td><td>270</td></tr><tr><td>10' coarse gravel</td><td>270</td><td>280</td></tr><tr><td colspan="2"></td><td></td><td></td></tr><tr><td colspan="2"></td><td></td><td></td></tr></tbody></table>				Type and color of material	From	To	top soil & clay	0	150	9' coarse gravel 1' sandy clay	150	160	5' sandy clay porous rock 5' gravel little	160	170	5' gravel and porous rock 5' porous rock loose	170	180	5' porous rock loose 5' porous rock little loose	180	190	2' porous rock 3' rock 5' coarse gravel little	190	200	6' gravel and porous rock 4' coarse gravel	200	210	7' sandy clay & clay 3' loose porous rock	210	220	10' loose porous rock	220	230	10' loose porous rock little clay	230	240	3' porous rock & clay 7' clay	240	250	1' clay 8' porous rock, clay, sandy clay 1' sand	250	260	4' med sand porous rock & clay 6' porous rock	260	270	10' coarse gravel	270	280									5 <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
				Type and color of material	From	To																																																					
				top soil & clay	0	150																																																					
				9' coarse gravel 1' sandy clay	150	160																																																					
5' sandy clay porous rock 5' gravel little	160	170																																																									
5' gravel and porous rock 5' porous rock loose	170	180																																																									
5' porous rock loose 5' porous rock little loose	180	190																																																									
2' porous rock 3' rock 5' coarse gravel little	190	200																																																									
6' gravel and porous rock 4' coarse gravel	200	210																																																									
7' sandy clay & clay 3' loose porous rock	210	220																																																									
10' loose porous rock	220	230																																																									
10' loose porous rock little clay	230	240																																																									
3' porous rock & clay 7' clay	240	250																																																									
1' clay 8' porous rock, clay, sandy clay 1' sand	250	260																																																									
4' med sand porous rock & clay 6' porous rock	260	270																																																									
10' coarse gravel	270	280																																																									
			6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well																																																								
			7 Casing: Material Steel Height: above/below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. Diam. 16 in. to 280 ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Weight 31 lbs./ft. L																																																								
			8 Screen: W.A. Brown Entegris Manufactured see below Dia. 16 " Type see below Slot/gauze 3/16 Length 40' Set between 240 ft. and 280 ft. Fittings: 3/4" Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material																																																								
			9 Static water level: 180 ft. below land surface Date																																																								
			10 Pumping level below land surfaces: 270 ft. after 10 hrs. pumping 400 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 400 g.p.m.																																																								
			11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date																																																								
			12 Well head completion: 12" <input type="checkbox"/> Pitless adapter <input checked="" type="checkbox"/> Inches above grade																																																								
			13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Puddled <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> clay Depth: From 0 ft. to 16 ft.																																																								
			14 Nearest source of possible contamination: ft. Direction Type Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																																								
			15 Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.m.p. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																																								
16 Remarks: elevation Cap welded on top - to be used at future time for water for to be added for two existing valleys sprinklers.				17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Jack Paine Drilling 197 Business name License No. Address McDonald Signed Jack Paine Date 7-15 Authorized representative																																																							