

1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SE 1/4 Section Number 15 Township Number T 6 S 6 Range Number R 2 E/W

County: Cloud Distance and direction from nearest town or city street address of well if located within city? 5 miles north of Aroua and 3/4 of mile west of Hushier Rd.

2 WATER WELL OWNER: Terry Ferguson RR#, St. Address, Box # Box 672 City, State, ZIP Code Concordia, KS 66901 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the SE corner of the SW quarter]

4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 45 ft. Depth(s) Groundwater Encountered: 1. 45 ft. 2. WELL'S STATIC WATER LEVEL: 40 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 25 gpm: Well water was 9 in. to 60 ft. and Bore Hole Diameter: 9 in. to 60 ft. and

WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter: 5 in. to 40 ft. Dia. 5 in. to 40 ft. Dia. Casing height above land surface: 2 in. weight 54 lb weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft. From 40 ft. to 60 ft. From 40 ft. to 60 ft. From 40 ft. to 60 ft.

GRAVEL PACK INTERVALS: From 25 ft. to 60 ft. From 25 ft. to 60 ft. From 25 ft. to 60 ft. From 25 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 25 ft. From 0 ft. to 25 ft. From 0 ft. to 25 ft. From 0 ft. to 25 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? Southwest How many feet? 300

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/15/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo/day/yr) 12/6/98 under the business name of Halderman Well Drilling by (signature) Gary Halderman

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.