WATER WELL RECORD Form WWC-5					Division of Wate	er Resources App. N	0.	
1 LOCATION OF WATER WELL:			Fraction		Section Number			
	nty: Gra		1/4 NW 1/4 SI	W 14 NW 14			R 21 □E ☑W	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:								
							(in decimal degrees)	
83 ft from W line & 1752 ft from N line					Longitude: (in decimal degrees)			
					Elevation:			
2 35/4	TED M	ELL OWNER: L&A Iol		Datum: WGS 8	4, 🔲 NAD 83, 🗌	NAD 27		
3			nnson Farms, LLC	Collection Method:				
RR#, Street Address, Box #: 3256 360th Ave						GPS unit (Make/Model:)		
City, State, ZIP Code : Bogue, KS 67625					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 120 ft.								
	TION BO							
	N	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr						
	Pump test data: Well water was ft. after hours pumping gpm							
NIW NE EST. YIELDgpm. Well water was								
W Bore Hole Diameter 8.5 in. to 120 ft., and in. to								
WELL WATER TO BE USED AS: □ Public water supply □ Geothermal □ Injection well								
Other (Specify below)								
Irrigation Industrial Domestic-lawn & garden Monitoring well								
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☐ No								
S If yes, mo/day/yr sample was submitted								
Water well disinfected? ✓ Yes □ No								
5 TYPE OF CASING USED: Steel P PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter 4.5. in to 120 ft., Diameter in to ft., Diameter in to ft.								
Casing height above land surface 18 in, Weight 2.5 lbs./ft., Wall thickness or gauge No. 0.248								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From 80 ft. to 120 ft., From ft. to ft.								
From ft. to ft.								
GRAVEL PACK INTERVALS: From 20 ft. to 120 ft., From ft. to ft.								
From ft. to ft. From ft. to ft.								
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other								
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Septic tank								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
		n well			rom well			
FROM	TO	LITHOLOG		FROM			GGING INTERVALS	
0	2	Surface						
2	10	Loess				·····		
10	25	Clay						
25	31	Sandy clay						
31	40	Fine sand						
40	47	Fine to some med sand w/ clay str						
47	69	Fine to med sand w/ clay str						
69	116	Fine to med sand w/ clay lens						
116	120	Black shale						
<u> </u>	TIO 120 DIGOR STIGIE							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo/day/year) .8/27/12 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 838 This Water Well Record was completed on (mo/day/year) 10/5/12								
under the business name of D&R Pump Service, LLC by (signature)								
INSTRUCTIONS: Use ty pewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blu	ue, pink) to	Kansas Depar tment of Health a	and E nvironment, Bureau	of Water. Geolog	ev Section, 1000 SW Jac	ckson St., Suite 420, 1	Toneka, Kansas 666 12-1367	
Telephone	785-296-	5524. Send one copy to WAT	ER WELL OWNER and	retain one for yo	our records. Include fee	of \$5.00 for each con	nstructed well. Vi sit us at	
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								

Check: White Copy, Blue Copy, Pink Copy