WATER WELL RECORD   Form WWC-5   Section of Water   Well ID
DOCATION OWN TERK WELL:
WELL OWNER: Last Name: Johnson   First: Corey   Business   State: Name: Johnson   First: Corey   Business   PO Box 86   State: KS   ZIP 67625   State: In our part of the control of the
Section Register State   Sta
Address
Address   City: Boaule   State: KS   ZIP. 67625   State: KS   ZIP. 67
SECTION BOX:   SCOUNTING   SECTION BOX:   SECTION BOX:   SECTION BOX:   A   A   A   A   A   A   A   A   A
Depth(s) Groundwater Encountered: 1)
WELL'S STATIC WATER LEVEL:
WELL WATER TO BE USED AS:
NW   NE
Pump test data: Well water was
Section   Sect
Well water was   fl.
Stimated Yield:gpm Bore Hole Diameter: _8.5. in. to80. ft. andgeneral Every   GPS   Topographic Map   Other
S
1. Domestic:   5
1. Domestic:   5
Household
Lawn & Garden
2.
Ingaton
Steel   Steel   PVC   Other   Steel   PVC   Other   Steel   Steel   PVC   Other   Steel   Steel   Steel   Steel   PVC   Other   Steel   Stee
Was a chemical/bacteriological sample submitted to KDHE?
Water well disinfected?
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Helded Threaded Casing diameter 5 in. to 80 ft., Diameter in. to 6. ft. Casing height above land surface 18 in. Weight 29 lbs./ft. Wall thickness or gauge No. 0.258
Casing diameter 5 in to 89 ft. Diameter in to ft. Diameter ft. Diamete
TYPE OF SCREEN OR PERFORATION MATERIAL:    Steel
TYPE OF SCREEN OR PERFORATION MATERIAL:    Steel
Brass   Galvanized Steel   Concrete tile   None used (open hole)   SCREEN OR PERFORATION OPENINGS ARE:   Continuous Slot   Mill Slot   Gauze Wrapped   Torch Cut   Drilled Holes   Other (Specify)   Continuous Slot   Mill Slot   Gauze Wrapped   Saw Cut   None (Open Hole)   SCREEN-PERFORATED INTERVALS: From 20 ft. to 80 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 80 ft., From ft. to ft., From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft. ft. From ft. to ft., From ft. ft., From ft. to ft., From ft. to ft., From ft. to ft., From ft. ft., From ft. to ft., From ft. ft., From ft. ft., From ft. ft. ft., From .
SCREEN OR PERFORATION OPENINGS ARE:  Continuous Slot Mill Slot Gauze Wrapped Saw Cut Other (Specify)  SCREEN-PERFORATED INTERVALS: From 20 ft. to 80 ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 20 ft. to 80 ft., From ft. to ft.  GROUT MATERIAL: Neat cement Cement grout Bentonite Other  Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.  Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Freilizer Storage Other (Specify)  Direction from well? Distance from well?  Distance from well? FROM TO LITHOLOGIC LOG FROM TO LITHOLOG (cont.) or PLUGGING INTERVALS  12 49 Fine to med sand  Vire Wrapped Saw Cut Drilled Holes Other (Specify) Other (Specify) Fine to some med sand w/ clay lens
□ Continuous Slot       □ Mill Slot       □ Gauze Wrapped       □ Torch Cut       □ Drilled Holes       □ Other (Specify)         □ Louvered Shutter       □ Key Punched       □ Wire Wrapped       □ Saw Cut       □ None (Open Hole)         SCREEN-PERFORATED INTERVALS:       From 20       ft. to 80       ft., From       ft. to       ft. from       ft. to       ft. to       ft.       ft. to       ft.
Louvered Shutter   Key Punched   Wire Wrapped   Saw Cut   None (Open Hole)
SCREEN-PERFORATED INTERVALS: From 20 ft. to 80 ft., From ft. to ft., From ft. to ft. from ft. from ft. to ft. from from from from from from from from
GRAVEL PACK INTERVALS: From 20 ft. to 80 ft. From ft. to ft., From ft. to
Grout Intervals: From
Nearest source of possible contamination:   Septic Tank
☐ Septic Tank       ☐ Lateral Lines       ☐ Pit Privy       ☐ Livestock Pens       ☐ Insecticle Storage         ☐ Sewer Lines       ☐ Cess Pool       ☐ Sewage Lagoon       ☐ Fuel Storage       ☐ Abandoned Water Well         ☐ Other (Specify)       ☐ Other (Specify)       ☐ Distance from well?       ☐ ft.         10 FROM       TO       LITHOLOGIC LOG       FROM       TO       LITHOL LOG (cont.) or PLUGGING INTERVALS         0       2       Surface       ☐ Surface       ☐ Distance from well?       ☐ Distance from well? <td< td=""></td<>
Septer Lines   Cess Pool   Sewage Lagoon   Fuel Storage   Abandoned Water Well   Watertight Sewer Lines   Seepage Pit   Feedyard   Fertilizer Storage   Oil Well/Gas Well   Other (Specify)   Direction from well?   ft.   ft.
Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well  Other (Specify)  Direction from well?  Distance from well?  TO LITHOLOGIC LOG FROM TO LITHOLOGIC INTERVALS  Surface  12
Other (Specify)
10 FROM     TO     LITHOLOGIC LOG     FROM     TO     LITHOLOG (cont.) or PLUGGING INTERVALS       0     2     Surface     2       2     12     Loess       12     49     Fine to med sand       49     72     Fine to some med sand w/ clay lens
0 2 Surface 2 12 Loess 12 49 Fine to med sand 49 72 Fine to some med sand w/ clay lens
2 12 Loess 12 49 Fine to med sand 49 72 Fine to some med sand w/ clay lens
12 49 Fine to med sand 49 72 Fine to some med sand w/ clay lens
49 72 Fine to some med sand w/ clay lens
75 Yellow ochre
72         75         Yellow ochre           75         80         Brown shale
Notes:
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, plugged
and this record is true to the best of my knowledge and belief.
under the business name of LOGA CUITO SHOWN LLOCK Signature Signature
Mail Libite copy along with a fee of \$5.00 for each constructed well to Kansas Denartment of Health and Environment, Bureau of Water, GWTS Section,
under the business name of D&R Pump Service. LLC.  Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,  1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.  KSA 82a-1212  Revised 7/10/2015