

1 LOCATION OF WATER WELL: County: Graham	Fraction C 1/4 SE 1/4 SE 1/4	Section Number 13	Township Number T 6 S	Range Number R 23 EW
--	--	-----------------------------	---------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?
11 North 1 East 1/2 North of Hill City, Ks.

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	F. & M. Bank Hill City, Ks.	Murfin Drilling Co. Box 661 Colby, Ks. 66701	Board of Agriculture, Division of Water Resources Application Number: T88 361
---	--	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 160 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 8.2 ft. below land surface measured on mo/day/yr 3-27-89
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter in. to ft., and in. to ft.	
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 <u>Oil field water supply</u> 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 <u>Lawn and garden only</u> 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 4.5 in. to 140 ft., Dia. in. to ft., Dia. in. to ft.			
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
3 Water tight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 140 ft. to 160 ft., From ft. to ft.		
GRAVEL PACK INTERVALS:	From ft. to ft., From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 <u>Cement grout</u>	3 Bentonite	4 Other
Grout Intervals: From 3 ft. to 6 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? Northwest		How many feet? 660	15 <u>Oil well/Gas well</u>	
			16 Other (specify below)	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
160	82	Gravel			
82	6	Clay			
6	3	Cement			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-27-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 394 This Water Well Record was completed on (mo/day/yr) 5-28-89 under the business name of Woofter Pump & Well Serv. by (signature) <i>Wall Woff</i>
--