WATER WEI	eridan rection from r	nearest tow	-w " ~	s of well if located with	74 C	on Number	Township Nu		nge Number
WATER WEI	rection from n	earest tow					1 0	5 R	100 EW
, R#, St. Addres	LL OWNER:								
, R#, St. Addres	LL OWNER:								
R#, St. Addres									
R#, St. Address, Box # : RR 1, BOX 12 ity, State, ZIP Code : Dresden, Ks 67635							Board of Agriculture, Division of Water Resources		
LOCATE WE	Code :	ON WITH	NS 07035				Application Nu	mber:	
AN "X" IN SE	CTION BOX	:	DEPTH OF COM	PLETED WELL	153	ft. ELE	VATION:		
	N		Depth(s) Groundwate	er Encountered 1		ft	t. <b>2</b>	ft. 3	ft.
X			WELL'S STATIC WA	TER LEVEL n	<b>a</b> ft. b	elow land s	surface measured o	on mo/day/yr	
N	w N	F	Pump tes	t data: Well water wa	as	1	ft. after	hours pumping	gpm
L Ti	``   ';	~	Est. Yield gpm: Well water was ft. a Bore Hole Diameter 8 in. to 160 ft. WELL WATER TO BE USED AS: 5 Public water supply  1 Domestic 3 Feed lot 6 Oil field water supply			1	ft. after hours pumping g		
w X		E				ft. and	and in. to ft.		
			WELL WATER TO B	EUSEDAS: 5 Publ	Public water supply 8 Air conditioning 11 Injection well  2) If field water supply 9 Dewatering 12 Other (Specify below)				
si	ws	E	2 Irrigation 4	Industrial 7 Law	n and narde	oppiy on (domaeti	ic) 10 Monitoring	i well	(openly below)
				eriological sample sub					
	S		submitted	enological sample sub	initied to D		ater Well Disinfecte		No
TYPE OF BL	ANK CASIN	G USED:		Wrought Iron	8 Concre			NTS: Glued X	
1 Steel	July Oroni			Asbestos-Cement					
2 PVC		4 ABS					•	Threaded	
lank casing dia	ameter			ft., Dia	in. to	)	ft Dia	in. to	ft.
asing height a	bove land su	rface	18 in	weight 2.	38	lbs./ft.	Wall thickness or	gauge No.	.248
YPE OF SCRI	EEN OR PER	REORATIO	N MATERIAL:	weight 2.			10 Asbe	estos-cement	
1 Steel			ess steel 5	Fiberglass	8 1	RMP (SR)	11 Othe	er (specify)	
2 Brass				Concrete tile	9 /	ABS	12 Non	e used (open hole)	
			NGS ARE:	5 Gauzed 6 Wire wra	wrapped		8 Saw cut		ne (open hole)
	uous slot ed shutter		Mill slot Key punched				9 Drilled holes		
CREEN-PERF			• •	3 ft. to		ft	From	ify)	ft
				ft. to					
GRAVE	EL PACK INT	ERVALS:	From 20	ft. to	153	ft.	From	ft. to	ft.
			From	ft. to		ft.	From	ft. to	ft.
GROUT MA	TERIAL:	1 Neat	cement 2 Ce	ment grout	3 Bent	onite	4 Other		
rout Intervals	From	0	ft. to 20	ft. From	ft. to	0	ft. From	ft. to	) ft.
			contamination:				stock pens	14 Abandoned	d water well
1 Septic tank						storage 15 Oil well/ Gas well			
2 Sewer lines			5 Cess pool 8 Sewage lago		-				
		nes	6 Seepage pit	9 Feedyard				n	one
FROM FROM		CODE	LITHOLOG	101.00	FROM	How man		UGGING INTERVA	u e
0	2		urface	IC LOG	155	160	Black shale	OGGING INTERVA	ilo
2	15		oess		100	100	Diagn origin		
15	26		ay						
26	29		ne to med sand						
29	65		ay & caliche						
65	80		ne to med sand						
80 85	85 91		aliche & clay andy clay w/cali	oho otrko		ļ			
91	96	S	andstone w/clay	& caliche strk		<del> </del>			
96	105		ne to med sand						
105	116		andy clay w/fine						
116	120	Fi	ne sand w/clay						
120	152		ne to md sd & g	ıravel					
152	155	Y	ellow ochre			L			
/	TOR'S OR L	ANDOWNE	R'S CERTIFICATION	: This water well was (	1) construct	ted, (2) reco	onstructed, or (3) plu	ugged under my juri	sdiction and was
_CONTRAC									
ompleted on (	mo/day/yr)		1-16-0	6	and thi	is record is	true to the best of	my knowledge and	belief. Kansas
ompleted on ( Vater Well Co	ntractor's Lic	ense No.	1-16-0	6 554 Pump & Well In answers. Send three co	This W	/ater Well F	Record was comple	ted on (mo/day/yr)	2-3-06