31		VV P	TER WELL RE	CORD F	orm WWC-		82a-1212 l	D 110. —	V 2-03			
LOCAT	ION OF WA	TER WELL:	Fraction			Se	ection Numb	per To	ownship Num	ber	Range I	
County: (NE 1/		1/4 NW		23	Т	6	s	R 3	E (W
ı			own or city stree		well if loca	ted within o	ity?					
Approxir	mately 2 1/4	miles south and	2 miles east of	Concordia								
2 WATER	WELL OW	NER: Cloud Co	untv RWD #1									
KK#, St. A	aaress, Bo	x # :Route 1 -	Box 59					В	oard of Agrice	ulture, Div	ision of Wa	ater Resource
City, State	, ZIP Code	Jamestov	vn, KS 66948					A	oplication Nu	mber:		
3 LOCATE	E WELL'S LO	OCATION WITH	4 DEPTH OF	COMPLETE	D WELL	72.70	ft. ELE	VATION:	unknown			
AN "X"	IN SECTION	N BOX:	 Depth(s) Grou	ndwater En	countered	1		ft. 2	rod on mo/da			
 			Depth(s) Grou WELL'S STATION	WATER LE	VEL 23.	50 ft. be	low land sur	face measu	red on mo/da	y/yr 4-21	-03	
1 T	.i.	i	Pur	np test data	: Well wate	r was no	checked	ft. after		hours pu	mping	gpm
-	_NW	NE	Est. Yield un									
0	1 1		Bore Hole Dian	neter8	in. to		90f	ft., and		in	i. to	ft.
- w - w - w	· · ·		WELL WATER				supply		onditioning		Injection w	
	i	i	1 Domestic	3 Feedlo			r supply		•			
-	- SW	SE						_	-	12	Other (spec	Jily Delow)
		1	2 Irrigation				wn & garden)	\sim	-			
	- 's		Was a chemical/	bacteriologica	al sample su	bmitted to D						
5 TVD5 0	SE DI ANICO		mitted			- Conor			isinfected? Y			
	F BLANK	CASING USED:		5 Wrought in		8 Concr			ASING JOIN			
1 Steel		3 RMP (SR)		6 Asbestos-		g Other	(specify below	N)				
②PVC		4 ABS		7 Fiberglas								
Blank cas	sing diamete	r 5	in. to	55 ft.,	Dia		n. to		ft., Dia			f
Casing he	eight above	land surface	32	in., weight		2.36		bs./ft. Wall	thickness or (gauge No	.2.	214
TYPE O	FSCREEN	OR PERFORA	TION MATERIAL	L:		7 PVC			10 Asbest	os-cement		
1 Stee	el	3 Stainless	steel	5 Fiberglas	ss	8 RMP	(SR)					
2 Bras	s	4 Galvanize	ed steel	6 Concrete	e tile	9 ABS			12 None u			
SCREEN	OR PERF	DRATION OPE	NINGS ARE:	5	Gauzed wra	pped		8 Sa	w cut		lone (open ho	ole)
1 Con	ntinuous slot	3	Mill slot		Wire wrappe	• •		9 Di	rilled holes			,
2 Lou	vered shutter	_	Key punched		Torch cut	-			ther (specify)			ft
1		ATED INTERVALS:	From	55	ft. to	70	ft., Fr			ft. to		ft.
1			From		ft. to		ft., Fr	rom.		ft to		f+
	GRAVEL	PACK INTERVAL	S: From	34	ft. to	70	ft., Fr			ft. to		ft.
			From		ft. to		ft., Fr	rom		ft. to		ft.
6 GRO	UT MATER	IAI · 1 Nont	cement 2 Cem		3 Bentoni			4 Other	Bontonito Holo			
ļ									Bentonite Hole		*************	
Grout Int	tervals: Fro	m	ft. to	ft., F	From	f	t. to	ft.	, From	0	ft. to	34 ft.
What is the nearest source of possible contamination: 10 Livestock pens								14 Abar	idoned water	well		
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel store							age 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage								16 Othe	er (specify bel	iow)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None known								own				
Direction t	from well?						How m	any feet?	~~	******		
	TO	I	ITHOLOGIC L	20		FROM		T T	DI UC	SING INT	EDVALC.	
FROM			LITHOLOGIC LO)G		FROM	то		PLUG	SING INT	ERVALS	
0	7	Topsoil	_									
7	35	Clay, brown,						ļ				
35	40	Clay, dark bro	own, soft									
40	53	Clay, light gra	y, medium to ha	rd								
53	55	Clay, light bro	wn									
55	67	Sand and gra	vel, coarse to fin	е								
67	71	Clay, light bro	wn with gravel									
71	73.5	Clay, black, s	oft									
73.5	85	Sand, very fin	е									
85	90	Sandstone										
120												
									<u> </u>			
7	I											
CONTRA			CERTIFICATION:		ll was (1) c	onstructed			(3) plugged		r my jurisdicti	
	on (mo/day			4-21-03						f my know		belief. Kansas
		's License No	185		s Water We	ell Record w	as complete	,	~ W /	11/1	4-25-03	
			ell & Equipment					by (signature	Comment of the second			
			n. <u>PLEASE PRESS FIR</u> 16620-0001. Telephone									nt of Health and