WATER WELL RECORD	Form WV	VC-5	Di	vision of Wate	r Resources App. N	o. L	
1 LOCATION OF WATER WELL:	Fraction					Range Number	
County: Sheridan		<u>% NW %</u>				R 30 DE WW	
Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here				Latitude: (in decimal degrees) Longitude: (in decimal degrees)			
890' from N Line, 918' from W line				Elevation: (in decimal degrees)			
			Datum	Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Dan Wachendorfer			Collec	Collection Method:			
RR#, Street Address, Box #: 11794 W Rd 130N				GPS unit (Make/Model:)			
City, State, ZIP Code : Selden, KS 67757				Digital Map/Photo, Topographic Map, Land Survey Est. Accuracy: 			
3 LOCATE WELL							
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL	154		ft.			
SECTION BOX: Depth(s) Ground							
	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr						
1 1 1	Pump test data: Well water was						
EST. YIELD	EST. YIELDgpm. Well water wasft. after hours pumping						
W Bore Hole Diameter 8.5 in. to ft., and in. to ft. WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SW SE							
Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted							
Water well disinfected? ✓ Yes □ No							
5 TYPE OF CASING USED: Steel P PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter 4.5 in to 154 ft. Diameter in to ft. Diameter in to ft.							
Casing height above land surface. 18 in., Weight 2.5 lbs/ft., Wall thickness or gauge No. 0.248							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
Steel Stainless Steel PVC Other (Specify)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Louvered shutter							
SCREEN-PERFORATED INTERVALS: From 114 ft. to 154 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 20 ft. to 154 ft., From ft. to ft.							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From .0 ft. to .20 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
Septic tank							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well							
Direction from well							
FROM TO LITHOLOG		FROM	TO	LITHO. LO	OG (cont.) or PLU	GGING INTERVALS	
0 2 Surface		150	154	Yellow och			
2 15 Loess							
15 30 Clay							
30 50 Fine sand w/ clay & ca							
50 61 Clay & caliche w/ sand	stone str						
61 82 Caliche						***************************************	
82 95 Caliche & sandstone							
95 110 Caliche, sandstone w/ 110 137 Fine to med sand w/ cl							
137 150 Sandy clay w/ some sand str							
under my jurisdiction and was completed on (mo/day/year) 10/19/12 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 838 This Water Well Record was completed on (mo/day/year) 11/16/12							
under the business name of D&R Pump Service, LLC by (signature)							
INSTRUCTIONS: Use ty pewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at							
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							